

REMARKS

Applicants have submitted herewith a Substitute Specification. The Substitute Specification does not contain new matter. A marked-up copy of the original specification showing the matter being added to and deleted from the specification is also submitted herewith. Claims 62-105 are pending in this application. Claims 1-61 have been canceled. Claims 62-105 have been added.

Conclusion

Entry of the above amendments is earnestly solicited. An early and favorable first action on the merits is earnestly solicited.

Should there be any outstanding matters that need to be resolved in the present application, the Examiner is respectfully requested to contact James M. Slattery (Reg. No. 28,380) at the telephone number of the undersigned below, to conduct an interview in an effort to expedite prosecution in connection with the present application.

If necessary, the Commissioner is hereby authorized in this, concurrent, and future replies to charge payment or credit any overpayment to Deposit Account No. 02-2448 for any additional fees required under 37.C.F.R. §§1.16 or 1.14; particularly, extension of time fees.

Dated: September 2, 2005

Respectfully submitted,

By 

James M. Slattery

Registration No.: 28,380

for #43,368
BIRCH, STEWART, KOLASCH & BIRCH, LLP
8110 Gatehouse Rd
Suite 100 East
P.O. Box 747
Falls Church, Virginia 22040-0747
(703) 205-8000
Attorney for Applicant

JC05 Rec'd PCT/PTO 02 SEP 2005

Highly-integrated analysis-chip with reactor at minimal-height reactor and its applications

DESCRIPTION

Field of the Invention

This ~~The present~~ invention ~~involves~~ relates to an analysis-chip, a kind with multiple reactors in particular. ~~To be more exact, it is~~ More specifically, to a highly integrated analysis-chip with minimal- height reactor. This ~~The present~~ invention involves also application of this the said analysis-chip.

Background of the invention BACKGROUND ART

Analysis-chip, chip in short, has been ~~applied in various fields,~~ extensive application, including the ~~determination of gene expression determination,~~ gene screening, drug screening, diseases diagnosis and treatment, environmental monitoring and management, ~~appraisal of justice, and~~ judicial identification etc.

The core of the chip is the reactor thereon, while the analysis-chip with markers also includes marking system. The three most important components of the reactor are: probe array, substrate and reactor structure. ~~Probe~~ The probe array is formed by immobilizing ~~probes~~ probe-ligand used ~~in for~~ analysis such as ~~polypeptide,~~ polypeptides, ~~nucleic acid acids~~ etc. onto the substrate surface through methods of spotting, printing etc. ~~Substrate~~ The substrate is usually a planar ~~carrier support~~ containing active derivative group groups, which is made of glass, metal, plastics or their derivatives in the ~~shape of rectangle, round or others~~ other shapes. At present, the mainstream substrate in use is made chiefly of glass and ~~the its~~ derivatives thereof (e.g. amino ~~group plate,~~ slides, aldehyde ~~group plate,~~ slides, epoxy ~~group plate and~~ polyamino slides and poly-amino acid-coated plate slides etc.) The reactor structure includes the partition structure, flow-path structure, ~~separation~~ separating structure, chamber structure, etc.

The rapid development of analysis-chip is closely related to its high integration technology, which involves the following four aspects facets: device miniaturization, high-density probe ~~array,~~ spots, multi-function integration, and high-density reactor ~~and integration of multi-functions~~. In the development of highly the high-integrated chip, significant ~~progresses have been made in the three aspects: the first is the highly~~ densified probe distribution (e.g. progress has been made in the first three facets (e.g. analysis-chip with high-density probe); the second is multi-functioned devices (e.g. chip-on-lab); the third is device miniaturization. However, with enhanced practical applications, new problems have emerged in the development of chip. For example, in polypeptide chip it is usually unnecessary to immobilize different types of probes, then of probe spots, chip-on-lab, etc). However, some problems rest. For example, in the polypeptide analysis-chip, only a few of different types of probe-ligand are needed, so what is the significance of high-density? the "high density"? Another example problem is: in the extensive diagnosis and screening, test device at low cost is needed, and then how could multi-function the "multi-function" be achieved at a

SUBSTITUTE SPECIFICATION (marked up)

low cost? The inventors of ~~this~~ the present invention hold that ~~the chip chips~~ with high-integration ~~and at low cost remains remain~~ one of the important aspects facets of analysis-chip development.

The current situation in chip development: of analysis-chip development:

1. Chip 1. analysis-chip and reactor partition structure

The foremost-developed chip, which is still in wide use today, is a an analysis-chip with no partition structure ~~(e.g., For example, an open non-flow analysis-chip with a single reactor based on microscope slide, is made through activation of a microscope glass slide and spotting the probe-ligands thereon, without other additional structures. advantages are: the structure is simple; spotting and scanning is easy and convenient; some processes can be performed while the media is in flowing status propelled by exterior forces (e.g. liquid spray for washing). Its disadvantage is: only one probe array is immobilized on the chip. When fewer types It is not necessary to fix many types of probes on every reactor, when only a few types (e.g., less than 100 types) of targets are to be detected in a sample, e.g., less than 100 types, and consequently not many types of probes are need to be fixed on every reactor, it is usually the ratio between probe region on substrate of reactor and the average substrate area on reactor that decides the cost of chip. Therefore, in order to reduce . Therefore, it is ratio between the area of the substrate probe region and the average area of the reactor substrate. In order to reduce the analysis cost, it is required to develop the chip with high density reactor. However, in the development of chip with high density reactor, one of an analysis-chip with a high density of reactors. However, one of the main problems to be solved for the development is the selection of appropriate reactor partition structure. structures. In addition, in order to reduce sample volume, volume of subjected sample, it is necessary to limit the flow of liquid media also has to be controlled. Moreover, the thickness of reactor partition structure has to be restricted on account of the wide applications of wide application of the optical scanning equipment. So, the partition structure with a height close closing to zero will make small smaller technical requirements on the scanning equipment. Meanwhile, the minimization of partition structure in height can also facilitate washing. facilitate reactor washing.~~

~~In order to increase benefit, manufacturers and researchers have made improvements on chips with no partition structure. As a result, Some chips with partition structure have been developed, which can be divided into two types: the detachable and the undetachable. Now a type of chip with undetachable partition structure available in market is a multi-reactor chip with detachable partition-structure and the multi-reactor chip with undetectable partition-structure. Now an available type with undetectable partition structure is an analysis-chip with multi-open non-flow reactors. Its basic structure is : upon a standard baseplate with a size of 25mm x 75mm or 26mm x 76mm (width x lengthheight), hydrophobic materials (surface substrate with a dimension of 25mmx75mm or 26mmx76mm (widthxheight), hydrophobic materials (water contact angle is 50-75°, e.g., polyester or PVC) are used to fabricate form a convex with a height of more than 0.5mm, and a width of over~~

SUBSTITUTE SPECIFICATION (marked up)

~~more than 1mm. Thereby a few to scores of several open reactors in round or square open reactors are formed on baseplate. shape are formed.~~ So, in this chip, the flow of liquid media is still controlled under control on the basis of the difference in height of partition structure. ~~In this type of chip, height difference between the partition structure and the plane of the substrate. In this case, if the partition area among open reactors is too low, the cross-contamination with neighbor reactors will occur; while however if it is too high, it will make a higher technical requirement on the biochip scanner.~~ Besides, another type of analysis-chip available at present is based on the structure of ELISA plate with a detachable partition structure, whose main drawbacks lie in the its complicated operation or the difficulty in minimization of its height or thickness of partition structures. ~~So, height of partition structure among reactors, which cannot be minimal.~~

~~So, despite various designs of partition structure(e.g. No.02145102.8 and 99114512.7 China Patent Application), how to develop an easily manufactured partition structure with minimal height at low cost remains one of concerned subjects. the concerns among analysis-chip developers.~~

~~2. Chip 2. analysis-chip and reactor flow-path structure, chip and reactor separation structure~~

At present, ~~microflow-micro-channel path, or microchannel micro-channel~~ is the chief flow-path structure and separation structure ~~widely studied. The microchannel usually is of on analysis-chip. The micro-channel, actually a concave flow-path, is usually less than 0.10mm in width and less than 0.025mm in depth. The analysis-chip with micro-channel path is called micro-channelled chip, e.g. So the current microflow path is actually a concave flow path.~~

~~The chip with microflow path is called microchannel chip; that is a comprehensive analysis-system in mininature with sampling, pre processing, liquid transporting and other analytic functions rolled into one, where microflow path serves as the network to connect micropump, microvalve, microvessel, microelectrode, microdetection units etc. The example for microchannel chip is the analysis-chip of Caliper Technologies Inc. (www.caliper.com). The advantages of microchannel biochip are micro-channelled analysis-chip are its high sensitivity and fast speed, while high speed, whereas the disadvantages are :~~ 1) ~~The microchannel as follows:~~

~~1) because the micro-channel has to be etched beforehand. Then, then after probe is deposited thereon, the microchannel micro-channel has to be sealed. With the such a complicated structure, industrialization is much the process of industrialization is very difficult;~~

~~2) In the in detection, the flow speed of liquid liquid flow speed has to be controlled by some sophisticated instruments, e.g. electronic osmosis device and etc.;~~

~~3) after reaction, because probe molecules are fixed on the inner surface, for some detections like inner surface, e.g. fluorescence-labeled detection, the test results cannot be read directly with a common biochip scanner. Despite various projects on microflow-micro-channel path recently (e.g. USA Patent No. 6176962 and 6180536), how to develop an easily manufactured flow-path structure at low cost remains one of~~

SUBSTITUTE SPECIFICATION (marked up)

concerned subjects: the concerns.

~~3. Chip and the structure of the reaction chamber~~ 3. analysis-chip and reaction structure

~~Reactor~~ The reaction structure of analysis-chip includes open reaction well cell and closed reaction-chamber. The analysis-chip with reaction-chamber is a closed chip, though parts of partition structure are still open. ~~Closed-chip includes flowing and non-flowing chips. There is a kind of closed non-flowing chip, during reaction reactor is closed, while washing and cleaning, seal layer is disclosed (refers to CN 1335501A). For the closed microarray flow chip, it can be referred to China Patent ZL 022229310. For the irreversible closed microarray flow chip, it can be referred to CN 2559986Y. For the reversible closed microarray flow chip, it can be referred to China Patent ZL 022229310, etc. Owing to ligand is fixed only on one surface of reaction chamber of the chips; it is difficult to satisfy the requirements for especially higher sensitivity. Particularly~~ The closed analysis-chip includes flow and non-flow ones. In the present analysis-chip, ligand is immobilized only on one of two planes of the reaction-chamber, that does not favorite the sensitivity augmentation. Especially, for the existing flow chips analysis-chip with the closed chamber, the dynamic conditions for ligand-target reaction and conditions for observing signal are the factors concerned taken into concern while designing. The In present analysis-chip, the movement of liquid phase media in the reactor, especially in the reaction-chamber of reactor, is completed achieved through: mechanic transport, the weight of liquid media itself, and the hydrophilicities of liquid-hydrophilicity of inlet structure or/and outlet structure or more than one type of, or their combinations. For the reaction-chamber, all of these are exogenous external liquid-delivering impetus. Of course, the top plane, bottom plane and wall of reaction-chamber usually possess hydrophilicity; but this kind of endogenous external liquid-delivering impetus of hydrophilicity only is weak. Consequently, on the recent closed microarray chip, while running going through a test, especially performing through the operations of media changing change, sometimes the distribution of liquid media in the reaction-chamber of reactor is insufficient. For example, when gas exists, it will inhibit the distribution of liquid media, thereby interfering test result. At present, there is one kind of capillary chip, wherein the reaction chamber is fabricated by immobilizing ligand onto a length of wall of capillary passage or a length of glass fiber structure which is inserted into the capillary (CN 2483395A). But, the inner wall of capillary or the structure of glass fiber, which could be inserted into capillary, is very slim, so it is unsuitable for manufacturing array chip. Besides, it is not allowed when using some signal reading equipments (e.g. laser con focal scanner) for reading signal directly under the condition of the existence of chamber top unit in the reaction-chamber. results.

~~4. Chip~~ 4. analysis-chip and marking system

As for the current chips, one type requires pre-deposited markers in the reactor e.g. China Patent (A low density biochip and the preparing method thereof, Patent Application No. 00129440.7), which will release, in which the marker is released

SUBSTITUTE SPECIFICATION (marked up)

instantly in testing, ~~while~~ whereas the other type requires that the marker solution be subjected to ~~sample~~ samples or to the reactor after probe-target reaction is completed. The latter ~~marking system~~, though of higher sensitivity, is difficult to operate. The former ~~marking system~~ is easier to ~~operate~~, ~~however, owing to Hook effect etc., execute, but~~ its test sensitivity is greatly decreased due to the Hook effect etc. When the former is to be adopted in analysis-chip analysis, in order-

~~When this type of marking system is adopted in chip analysis,~~ to avoid Hook effect, all the markers should be in liquid status, ~~which, if needed, is and~~ subjected into reaction device completely through a mechanic system if necessary. For example, when the planar analysis-chip with outlaying an outlaid marking system and channel a channeled analysis-chip with inlaying an inlayed marking system ~~to~~ are employed in analysis, the special marker solution loading subjecting procedure and the corresponding mechanic system are required. In other words, in the ~~present prior~~ analysis-chip analysis, since the labeling procedure is to be carried out with a mechanic system which helps deliver markers, the special marker container, marker-delivering channel, converter for the delivered material and conversion procedures converting procedure are usually indispensable, thus making the test device complicated. Besides, since only a small amount of marker is needed in ~~the~~ detection, ~~the but~~ its storage and preparation of markers in both marking systems are ~~much~~ very troublesome. Though the ~~present microchannel prior micro-channeled analysis-chip~~ is equipped with inlaying an inlayed marking system, markers are released instantly in detection, therefore special procedure for adding the marker solution and corresponding mechanic system are required.

5. Reactor-protecting system

As chip with high-density of reactors is introduced, one important but often neglected problem in ~~its~~ the applications is: if only M out of N reactors ($N > M$) are used in ~~one~~ testing, how to preserve ~~other N-M~~ the extra reactors for later use-? The solution to this problem ~~serves as~~ is the prerequisite for developing chip chips with high-density of reactors at low-cost. As for the analysis-chip with a single reactor, the reactor-protecting system at present is actually a protecting system for the whole chip, which usually is a plastic box containing analysis-chip rack (grid) racks. But strangely, the analysis-chip with multi-reactors now in use is equipped with no special protecting structure but ~~the~~ said protecting plastic box for the analysis-chip with a single reactor.

Thus, the analysis-chip constituted by the present reactor partition structure, reactor flow-path structure, reactor separation separating structure, marking system and reactor-protecting system are yet to be ~~further~~ improved.

DISCLOSURE OF THE INVENTION

SUMMARY OF THE INVENTION

The ~~purpose of this~~ primary object of the present invention is to provide a highly

SUBSTITUTE SPECIFICATION (marked up)

integrated analysis-chip and the corresponding devices, which should be of easy preparation, lower cost, high sensitivity, small sample consumption, simple operation, and homogeneous distribution of reaction media.

~~In the course of developing biochip for blood screening, tumor marker detection, and hepatitis screening, in order to render the researched chips to have more competitiveness at cost besides better quality than recently used ELISA reagent kit, we realized that to improve the utility of substrate, one of factors for controlling the cost of chip, or in other words, to improve integration of the~~ fact, the improvement of integration of the analysis-chip ~~is one of the keys to the problem solution.~~ In addition, ~~we also found that it is also~~ very important to simplify operation procedures, facilitate washing, lower the height of the reactor structure and consequently reduce the investment on ~~scanner~~ scanners by lowering the technical requirements ~~on it in detection.~~ Hence, "minimizing the height of the reactor structure and maximizing the integration level" become our important research subjects, which results in ~~this invention.~~ the present invention.

~~The goal of this invention is fulfilled through following fashions:~~

~~So,~~ the first embodiment of ~~this~~ the present invention provides an analysis-chip, which comprises one or more reactors with minimal height, wherein said reactor comprises at least:

1). one or more striped-capillary reaction-chambers, wherein said reaction-chamber comprises:

- i). top plane and bottom plane with a width more than ~~600um~~ 600um;
- ii). probe-ligand and substrate probe-region in which said probe-ligand is immobilized;
- iii). closed partition-structure with a height of 1-1000um, optimally 1-500um; and
- iv). inlet and outlet,

2). reactor structure with minimal-height; which comprises at least open partition-structure comprising:

- i). substrate blank region with a width of 0.5-10mm; or/and
- ii). one or more following convexes with a height less than 1000um, optimally less than 500um: hydrophobic convex, highly-hydrophobic convex, and water-absorbing convex; and optionally,
- iii). convex flow-path comprising high-hydrophilic convex with a width of 5-4000um, and a height of 0.05-1000um, optimally 0.05-500um relative to said substrate probe region; and optionally, reactor-protecting structure comprising protective unit with a distance less than 1000um, optimally less than 500um from said substrate probe-region; and optionally,

3). marking-system convex, a marker-containing convex that does not cover said probe-ligand, wherein:

(1). said top plane and bottom plane are parts of top unit and bottom unit of said striped-capillary reaction-chamber, respectively;

(2). said substrate probe-region is on said top plane or/and bottom plane;

(3). said closed partition-structure is placed between said top plane and bottom

SUBSTITUTE SPECIFICATION (marked up)

plane;

(4). material and dimension of said planes, and distance between said top plane and bottom plane are such that the capillary phenomenon of analysis media can take place in said striped-capillary reaction-chamber;

(5). said substrate blank region and substrate probe region are on the same plane of a same substrate, which presents a water-absorptivity less than 0.1g/g and a water contact angle as 40-80°;

(6). said highly-hydrophobic convex contains, at least in its partial surface, highly-hydrophobic material, wherein said highly-hydrophobic material presents a water contact angle of 40° bigger than that of said substrate probe region;

(7). said hydrophobic convex contains, at least in its partial surface, hydrophobic material, wherein said hydrophobic material presents a water contact angle as 55-80°;

(8). said water-absorbing convex contains, at least in its partial surface, water-absorbing material, wherein said water-absorbing material presents a water-absorptivity more than 0.1g/g;

(9). said highly-hydrophilic convex contains, at least in its partial surface, highly-hydrophilic material, wherein said highly-hydrophilic material presents a water contact angle less than 40°; and

(10). said protective unit closes at least partially said reactor structure when no sample is subjected, and it is irreversibly removed completely or partially when sample is to be subjected.

The striped-capillary reaction-chamber of analysis-chip of the first or second embodiments of ~~this~~ the present invention differs from the reaction-chamber of the ~~present prior~~ closed-flow-chip: the former is characterized by its requirement on the selection of material and dimension of said planes, and distance between said top plane and bottom plane, so that the capillary phenomenon of analysis media can take place in said striped-capillary reaction-chamber. Whereas the latter lacks such requirements which make it necessary to introduce other media distribution mechanism, such as putting a membrane in the chamber etc.

The striped-capillary reaction-chamber of ~~this~~ the present invention differs from the reaction-chamber of the ~~present prior~~ micro-channeled analysis-chip: 1). the former presents wider substrate probe region (>500μm) for immobilizing bigger probe array, whereas the latter narrow substrate probe plane (<500μm); 2) the former can apply the capillarity with much bigger flow for direct media distribution; but the latter applies the capillarity with only tiny flow, which requires additional energy for media distribution.

The striped-capillary reaction-chamber of ~~this~~ the present invention differs from the ~~present prior~~ capillary analysis-chip: the capillary structure of the former is formed by two planes as well as the structure between the two planes, which make it possible to fix a bigger probe array there, whereas the latter couldn't.

The top plane and bottom plane of the striped-capillary reaction-chamber of the analysis-chip of ~~this~~ the present invention could be in various geometric figures like rectangular, round etc. The materials of the top plane or/and bottom plane, especially the material for the substrate probe region could be selected from one of the following

SUBSTITUTE SPECIFICATION (marked up)

or their optional combinations: glass, silicon and silicide, metal oxide, metals and polymer materials as well as their derivatives etc. The probe array can be in various ordered distributions like matrix, broken lines, real lines etc. In fact, according to the various applications of chips, it can have and must have various selections of ordered ligand-distribution patterns. Said probes can be selected from one material of the following groups or their optional combinations: antigens, antibodies, ligand, aptamer screened by Systematic Evolution of Ligands by Exponential Enrichment (SELEX), polypeptides, single-strand or multi-strand DNA, nucleotides, polynucleotides, saccharides, coenzymes, cofactors, antibiotics, steroids, viruses and cells.

~~The convex flow path of the invention especially differs from the microflow path of present chips. The flow path of the latter needs to make channel, trough or eapping, and is a concave flow path, nits manufacturing is complicated and its cost is expensive.~~ In one analysis-chip of the first embodiment of the present invention, said convex is formed by solidifying liquid substance or/and fixing solid substance onto surface of said chip, wherein: 1). said liquid substance includes solution, paint, gel, emulsion which contain said highly-hydrophobic, hydrophobic, highly-hydrophilic and water-absorbing materials respectively; and 2). said solid substance includes plate, film, board, tape, and powder which contain said highly-hydrophobic, hydrophobic, highly-hydrophilic and water-absorbing materials respectively.

~~This invented convex of marking system can be in various geometric figures, such as dot, line, strip, sphere etc.~~ In fact, in the present invention, said highly-hydrophobic convex, hydrophobic convex, highly-hydrophilic convex, water-absorbing convex are made respectively through solidifying liquid material onto the analysis-chip surface, or/and immobilizing solid substance onto the analysis-chip surface. Said liquid materials include solution, paint, gel or emulsion containing highly-hydrophobic material, hydrophobic material, highly-hydrophilic material, and water-absorbing material respectively. Said solid substances include plates, films, boards, tapes or powder containing highly-hydrophobic material, hydrophobic material, highly-hydrophilic material, and water-absorbing material respectively. The following example indicates how said convex is prepared through solidifying liquid material: A). provide the liquid material that has affinity to the substrate; B). coat it onto the specified position of the substrate; C). solidify the coating through drying or/and adding solidifying agents, wherein the solidifying reactions include oxidation polymerization (e.g. in case of the modified paint with drying oil etc.), solvent volatilization (e.g. in case of varnish dried and solidified at normal temperature etc.), solidification through using solidifying agent, solidification through heating, catalysis through bio-enzyme (e.g. nature lacquer etc.) and so on. The following example indicates how said convex is prepared through immobilizing solid material: A). provide the shaped solid substance which can bind to the substrate; B). bind the solid substance onto the specified position of the substrate through adhesion or/and thermal fusion.

~~In this invented chip, the optimized pattern for said~~ The second embodiment of the present invention provides an analysis-chip, which comprises one or more flow or

SUBSTITUTE SPECIFICATION (marked up)

non-flow reactors with minimal-height, wherein said reactor comprises at least one or more striped-capillary reaction-chamber is: the chambers with a height of less than 1000 μ m, optimally 500 μ m, and optionally, reactor-protecting structure, wherein said reaction-chamber comprises:

- 1). top plane and bottom plane with a width more than 600 μ m;
- 2). probe-ligand and substrate probe-region in which said probe-ligand is immobilized;
- 3). closed partition-structure with a height of 1-1000 μ m, optimally 1-500 μ m; and
- 4). inlet and outlet, wherein:

(1).said top plane and bottom plane are parts of top unit and bottom unit of said striped-capillary reaction-chamber, respectively;

(2). said substrate probe-region is on said top plane or/and bottom plane;

(3). said closed partition-structure is placed between said top plane and bottom plane;

(4). material and dimension of said planes, and distance between said top plane and bottom plane are such that the capillary phenomenon of analysis media can take place in said striped-capillary reaction-chamber; and

(5). said substrate probe-region presents a water-absorptivity less than 0.1g/g and a water contact angle as 40-80°.

In fact, the chip of the second embodiment is the analysis-chip with striped capillary reaction-chamber. Said reactor is flow or non-flow one. The situation of probe immobilization includes three patterns: the probe is immobilized on the top-plane substrate, immobilized on the bottom plane substrate, or immobilized respectively on the top-plane and bottom plane substrates, wherein the top plane is on the top unit, and the bottom plane, bottom unit. Positions of the inlet and the outlet include at least three patterns: they are on bottom unit, on top unit, and in between the bottom and top units. For the differences between the analysis-chip with striped capillary reaction-chamber of the second embodiment and the prior closed flow chip, micro-channeled chip, and capillary chip, please refer to that in the first embodiment for details.

In one analysis-chip of the first embodiment or the second embodiment of the present invention:

1). said closed partition-structure presents a height of 1-300 μ m, optimally 30-100 μ m;

The 2). said top plane presents a width of 1000-15000 μ m and a length more than 1000 μ m; and

the 3).said bottom plane presents a width of 1000-15000 μ m and a length more than 1000 μ m.

In the striped-capillary reaction-chamber, the widths width of liquid-said inlet and liquid-or outlet are may be equal to or not equal to the widths width of the top plane and or bottom plane, and the their heights are may be equal to or not equal to the space between said top plane and bottom plane. We have discovered, in the situation of utilizing capillarity to distribute media directly, it is necessary to maintain certain chamber height (e.g. 30 μ m)-of-chamber 30 μ m). Besides, we have also discovered, when using mechanic force to distribute reaction media, it is beneficial to maintain

SUBSTITUTE SPECIFICATION (marked up)

certain height of chamber is ~~beneficial~~ for avoiding uneven ~~distributions~~ distribution, such as air bubble, etc.

~~In this invented chip, the optimized pattern for one analysis-chip of the first embodiment or the second embodiment of the present invention, the striped-capillary reaction-chamber is: the widths presents a width of the top plane and bottom plane are 1500-15000mm, preferably 2500-15000mm. 15000μm, preferably 2500-15000μm.~~

~~In this invented chip~~ In one analysis-chip of the first embodiment or the second embodiment of the present invention, said closed partition structure includes one or more of the following reversible or irreversible enclosing structures:

- 1). thermal enclosing structure;
- 2). chemical enclosing structure;
- 3). reversible or irreversible adhesive layer;
- 4). highly-hydrophobic layer;
- and
- 5). mechanic enclosing unit including coating, plate or tape of elastic polymer.

Said closure mainly refers to ~~the closure that~~ of borders between top ~~unit~~ and bottom ~~unit~~ units except liquid-inlet and liquid-outlet. The closure is mainly is the irreversible closure generated formed by the ways including adhesion or/and heat-fusion, -or/and HF or sodium silicate linkage at low ~~temperature~~ temperatures. The closure of adhesion can be irreversible closure or reversible closure. The closure formed by highly-hydrophobic water-partition seal and mechanic seal mainly is reversible closure. For irreversible closure, ~~when if~~ necessary, the top ~~plane~~ or bottom ~~plane~~ planes can be opened by mechanical action ~~to open the chamber cover force~~. Said mechanical seal units all possess a certain elasticity, for example, their Shore hardness are between 20-100°, and are made from rubber (e.g. natural rubber and the derivatives thereof; synthetic rubbers like acrylonitrile-butadiene rubber, butyl rubber, fluororubber, silicone rubber, fluorosilicone rubber etc.) and various organic polymers (e.g. organosilicon polymer, fluoropolymer, polycarbonate, plastic etc.).

~~In this invented chip, the one analysis-chip of the first embodiment or the second embodiment of the present invention, said top unit or/and bottom unit of said reaction-chamber present a thickness less than 1mm, optimally less than 0.2mm, and a detecting-light transparency rate more than 90%. In this invention, the One example for the transparent unit is a cover glass or activated cover glass with a, whose height of is 0.15mm. So, Hence the test result on the invented analysis-chip can be visualized directly with a signal-testing instrument. Said signal-testing instrument includes laser confocal scanner scanners and laser scanner. scanners. In the implementation examples embodiments, when the cover glass of the top unit is thin enough (e.g. □ 10.15mm), the invented chip, unnecessary to be dismantled, can be used directly for the scanning with scanner, showing no obvious differences of the results between using a cover glass or not. m0.15mm), it is not necessary to dismantle the invented analysis-chip before the scanning, for there is no obvious difference in the results with a glass cover or not.~~

~~In this invented chip~~ In one analysis-chip of the first embodiment or the second embodiment of the present invention, said probe-ligand is immobilized on either said top plane or said bottom plane,

SUBSTITUTE SPECIFICATION (marked up)

wherein said plane with said immobilized probe-ligand presents hydrophilic property whereas said plane without said immobilized probe-ligand presents hydrophobic property.

The In one analysis-chip of the first embodiment or the second embodiment of the present invention, said top plane is made of glass material whereas said bottom plane is made of hydrophilic or hydrophobic plastic.

In one analysis-chip of the first embodiment or the second embodiment of the present invention In this invented chip, one or more said probe-ligands are immobilized in one area whereas one or more ligats ligate of said ligands are immobilized in one other area in said probe region. Said, wherein said ligand and ligate include antigen and antibody, such as antibody and anti-antibody which are corresponding to said antigen etc. So this invented chip provides a new tool with high sensitivity, which can be used for detecting antigen and corresponding antibody simultaneously, antigens as well as the corresponding antibodies simultaneously.

In this invented chip, said convex flow path refers to a coating with said highly-hydrophilic material. When necessary, said convex flow path comprises hydrophobic convex or/and highly hydrophobic convex as its partition. The third embodiment of the present invention provides an analysis-chip, which comprises one or more open reactors with minimal-height, wherein said reactor comprises probe-ligand, substrate probe region, open partition-structure with minimal height, and optionally, reactor-protecting structure, wherein said convex open partition-structure comprises:

- 1). substrate blank region with a width of 0.5-10mm;
- 2). highly-hydrophobic convex or/and water-absorbing convex, all of which presents a height less than 1000 μ m 1000 μ , optimally less than 500 μ m. 500 μ m relative to said substrate probe region, wherein:

In this invented chip, said convex flow path can has separation media immobilized. Said separation media include electrophoresis media or chromatography media(1). said substrate blank region and substrate probe region are on the same plane of a same substrate, which present a water contact angle as 40-80°;

(2).

said highly-hydrophobic convex, hydrophobic convex, highly hydrophilic convex, water absorbing convex are made respectively by solidifying liquid material onto the surface of the chip, or/and immobilizing solid substance onto the surface of the chip. Said liquid materials include solution, paint, gel or emulsion containing contains, at least in its partial surface, highly-hydrophobic material, wherein said highly-hydrophobic material, highly hydrophilic material, and water absorbing material respectively. Said solid substances include plate, film, board, strip or powder containing highly hydrophobic material, hydrophobic material, highly hydrophilic material, and presents a water contact angle of 40° bigger than that of said substrate probe region; and

(3). said water-absorbing convex contains, at least in its partial surface, water-absorbing material respectively., wherein said water-absorbing material presents a

SUBSTITUTE SPECIFICATION (marked up)

water-absorptivity more than 0.1g/g.

~~The following example indicates how said convex is prepared by solidifying liquid material: A. providing the liquid material that has affinity to substrate; B. coating it onto the specified position on the substrate; C. solidifying the coating by drying or/and adding solidifying agent, wherein the solidifying reactions include oxidation polymerization (e.g. in case of the modified paint with drying oil etc.), solvent volatilization (e.g. in case of varnish dried and solidified at normal temperature etc.), solidification by using solidifying agent, solidification by heating, catalysis by bio-enzyme (e.g. nature lacquer etc.) and so on.~~

~~The following example indicates how said convex is prepared by immobilizing solid material: A. providing the shaped solid substance which can bind to substrate; B. binding the solid substance onto the specified position on the substrate by adhesion or/and thermal fusion.~~

In this invented chip, the height of said In fact, the analysis-chip of the third embodiment includes the following chips of the present invention: the analysis-chip with highly-hydrophobic partition structure, the analysis-chip with water-absorbing partition structure and the analysis-chip with highly-hydrophobic/water-absorbing partition structure. The example for highly-hydrophobic/water-absorbing complex convex is: the highly-hydrophobic convex is optimally near the substrate probe region whereas the water-absorbing convex is away from it. The convex herein can form various geometrical figures on the surface of substrate, such as single lines, multi-lines, strips, lattices etc. The invented open partition-structure with minimal height can be applied to all types of chips, such as the analysis-chip whose smallest space among reacting wells is 20% longer or more than the width of the reacting wells on its outstretched line; such as the analysis-chip with feeding structure or/and liquid-out structure; such as the analysis-chip with one or more structures that control the directional flow speed of the reaction media on the inlet and outlet area of the reactor; such as double-plane analysis-chip etc.

The invented open partition-structure with minimal height contains the substrate blank region with a width bigger than 0.2mm, located on the same plane of the substrate probe region, which is very important and indispensable for chips. Differing from the devices like the microwell plate for ELISA immobilized with one type of probe, the reactors of the invented analysis-chip are usually immobilized with the arrays of varied types of probes therein, demanding the uniformity of the reaction circumstances for every probe in the array. But the existence of highly-hydrophobic convex or water-absorbing convex or highly-hydrophobic/water-absorbing complex convex will change the reaction condition in its peripheral. Therefore, it is necessary to make a region between the substrate probe region and the convex, in which no efficacious probe is immobilized (the substrate blank region). Through numerous experiments, we have found that the width of the substrate blank region depends mainly on the height of convex and the water contact angle of highly-hydrophobic material or the absorptivity of water-absorbing material.

In one analysis-chip of the first embodiment or the third embodiment of the present

SUBSTITUTE SPECIFICATION (marked up)

invention, said highly-hydrophobic convex presents a height of 0.1-100 μ . In fact, in the ~~implementation~~ examples, when its height is 20-50 μ , desirable results ~~can be obtained~~ become obtainable.

In our research on analysis-chip, we have found that high-hydrophobicity, as a kind of can be used as an independent reactor-partition mechanism, ~~can effectively confine for limiting water solution to movement on~~ the surface of hydrophilic substrate surrounded by highly-hydrophobic material. Table 1 reveals the effects of some highly-hydrophobic coatings:

Table 1 ~~partition~~ Partition effects of some highly-hydrophobic coatings

Highly-hydrophobic paint	Static water contact angle	The width of coating	The thickness of coating	Surface area of hydrophilic substrate	The loading <u>subjecting</u> quantity of water	Down flow at 90°
Organosilicon paint	95°	1mm	30-40 μ	16mm ²	20 μ l	-
Nano-textile	155°	1mm	400 μ	16mm ²	30 μ l	-
Nanometer silica CDJ7	160°	1mm	20-30 μ	16mm ²	30 μ l	-
Black paint (ChuangKePeng)	85°	1mm	<5 μ	16mm ²	15 μ l	-
Substrate without coating	45°	-	-	16mm ²	10 μ l	+

In the table, ~~down~~“down-flow at 90°” means making the analysis-chip vertical to the horizontal plane then observing whether there is the flow of water. When water does flow downward, the result is positive (+), ~~while~~ when there is no water flow, the result is negative (-).

In ~~this invented chip~~ one analysis-chip of the first embodiment or the third embodiment of the present invention, said highly-hydrophobic material presents a water contact angle that is over 70°bigger than that of said substrate probe region; ~~preferably over 90°, especially preferably over 110°.~~

~~In this invented chip~~ In one analysis-chip of the first embodiment or the third embodiment of the present invention, said highly-hydrophobic material presents a water contact angle that is over 90°bigger than that of said substrate probe region.

In one analysis-chip of the first embodiment or the third embodiment of the present invention, said highly-hydrophobic material presents a water contact angle that is over 110°bigger than that of said substrate probe region.

In one analysis-chip of the first embodiment or the third embodiment of the present invention, said highly-hydrophobic material includes highly-hydrophobic organic material or/and highly-hydrophobic nano-material.

In one analysis-chip of the first embodiment or the third embodiment of the present invention, said highly-hydrophobic material includes one or more of the following materials:

- 1). highly-hydrophobic organosilicon and its derivatives;

SUBSTITUTE SPECIFICATION (marked up)

- 2). highly-hydrophobic fluoro-resin and its derivatives;
- 3). highly-hydrophobic polymer; and
- 4). paint or/and solid substance containing highly-hydrophobic nano-particle.

Said organosilicon materials are organosilicon polymer, copolymer based on organo-siloxane bond, or the their highly-hydrophobic derivatives thereof. Said fluoro-resins include: fluoro-resin oligomer, polytetrafluoroethylene (PTFE), copolymer fluoro-resin (PFEP), polytrifluorochloroethylene, and polypolyvinylidene fluoride. Said highly-hydrophobic polymers include highly-hydrophobic polypropylene, polyacrylate and the their derivatives thereof. In the coating or/and solid substance with said highly-hydrophobic nanoparticle, said nanoparticles include one or more of the following nanoparticles with a whose diameter of is 1nm-100nm: gold, vanadium, lead, silver, iron and oxide powders thereof, silica, titanite oxide, alumina powders and the derivatives thereof: their derivatives.

~~In this invented chip, said hydrophobic convex includes hydrophobic coating, said hydrophobic coating includes colored hydrophobic line, or/and colored hydrophobic strip.~~

~~In this invented chip, said highly hydrophobic material presents a surface static water contact angle of less than 30°. Said highly hydrophilic materials include highly hydrophilic nanometer material (e.g. highly hydrophilic nanometer material) and highly hydrophilic polymer material (e.g. highly hydrophilic polyacrylate acid paint).~~

~~As one of the designs for invented analysis chips~~ In one analysis-chip of the first embodiment or the third embodiment of the present invention, said water-absorbing material includes one or more of the following:

- 1). natural water-absorbing material;
- 2). solid porous material of hydrophilic inorganic compound; and
- 3). water-absorbing material of synthetic polymer.

In one analysis-chip of the first embodiment or the third embodiment of the present invention, said water-absorbing material includes one or more of the following:

- a). capillary-structure-containing paper product, cotton product, or/and sponge as well as their modified materials,
- b). calcium salt;
- c). water-absorbing materials based on cellulose or its derivative,
- d). water-absorbing materials based on starch or its derivative,
- e). water-absorbing materials based on synthetic resin as well as compound generated by grafting, blocking and copolymerizing, paper product, cotton product, sponge and its modifier, calcium salt, water-absorbing cellulose material, water-absorbing starch material, and water-absorbing synthetic resin produced by grafting, blocking and copolymerizing.

~~Said marking system convex refers to convex of controlled marker releasing system, wherein said controlled marker releasing system comprises marker and presents a half-releasing period of said marker of more than 10 seconds, optimally~~

SUBSTITUTE SPECIFICATION (marked up)

~~more than 30 seconds, wherein said marker comprises labeling reagent and marking ligand,~~

~~The example for controlled release marking system is the programmable release system, in which the release velocity and the lag time of marker are defined mainly by the compositive material and structure of system itself. For the marker in said convex of marking system, the labeling methods include chemiluminescent labeling, excitation luminescent labeling, non selective light reflection labeling and selective light reflection labeling. Wherein 1). said labeling reagent includes one or more of the following reagents: enzyme, fluorescent dyestuff, chemiluminescent catalyst, nonferrous metal or nonferrous metallic salt, dyestuff and paint;~~

~~and 2). said ligand includes one or more of the following substances: antigen, antibody, biotin, drug ligand polypeptides, DNA, RNA and the fragments thereof.~~

~~In this invention, the term "half releasing time" refers to the time needed to release 50% of markers from controlled marker releasing system into reactor under the condition of labeling reaction. Obviously, this invented marking system is a controlled marker releasing system. The convex with controlled marker releasing system can be of various technical designs, for instance, it can be made into a sphere or other solid figures containing liquid or solid markers and the release retarder; or a dot or line etc. with markers and release retarder. In these cases, the marking convex presents a height less than 1000 μ m, and is fixed around the array of said probe ligand in said reactor or inside the array of said probe ligand to form an array of probe ligand and marking system.~~

~~As one of designs for the invented chips, said controlled marker releasing system comprises said marker and controlled releasing agent.~~

~~The release retarder described in this invention refers to the materials that can controll or take part in controlling the releasing speed of markers and delay the releasing, such as the diffusion controlling agent that controls the release of markers by controlling the density of the controlling agent in the network; the chemical reaction controlling agent that controls the release by controlling degradation; solvent activation controlled release agent that controls the release by controlling the activation process (e.g. dissolving); the release retarders that speeds up release by using water absorbing and swelling materials inside membrane to make membrane dilate and disintegrate and etc.~~

~~With diffusion controlling system, the markers are released according to the fluctuation of density of diffusion controlling agent (e.g. polymer with moderate solveney and dilatability) in the network; with chemical reaction controlling system, markers are released when the controlling agent (e.g. degradable polymer) is degraded; with activation controlling system, markers are released when the controlling agent (e.g. membrane) is activated (e.g. dissolved) by solvent.~~

~~For example, in diffusion controlling system with markers evenly dispersed or embedded in polymer with moderate water solubility (release retarder), the releasing speed of markers is decided by the dissolving and swelling speed of polymer, thereby~~

SUBSTITUTE SPECIFICATION (marked up)

~~the concentration of marker can be adjusted to accommodate the requirement in different testing procedures.~~

~~For another example, in chemical reaction controlling system with markers evenly dispersed or embedded in the degradable polymer (release retarder), the marker-releasing velocity is actually zero when sample is subjected. While labeling, markers are released due to the degradation of polymer with the help of degrading agent (e.g. enzyme). For still another example, in activation controlling system made up of markers and membrane (release retarder), the release or delayed release of marker is decided by the speed of membrane dissolution and dilation.~~

~~As one of designs for the invented chips, said convex of controlled marker-releasing system includes mono sandwiched or multi sandwiched structure made up of said marker and controlled-releasing agent, wherein said sandwiched structure refers to structure where the concentration of said marker is higher inside than outside.~~

~~In multi-sandwich structure, one or more types of markers and one or more types of release retarders could be comprised, such as, the first layer may comprise marker; the second layer may comprise the structure of enhancing agent.~~

~~As one of designs for the invented chips, said controlled-releasing agent includes water-soluble organic compound or organic compound that will disintegrate in water solution. said organic compound includes one or more of the following materials: carbohydrate and its derivatives thereof, plant starch and modified starch, plant glue, animal glue, modified cellulose, polymer and condensate.~~

~~As one of the designs for the invented analysis chips, said protecting unit includes one or more of the followings: organic film or/and plate, film or/and plate of metal-organic complex, and slide.~~

~~Said protecting unit is connected with the reactor through one or more of the following reversible/irreversible enclosing structures: thermal enclosing structure, chemical enclosing structure and reversible or irreversible adhesive layer.~~

~~As one of designs for the invented chips, said protecting unit is pre-cut for the convenience of possible removal.~~

~~According to another aspect of the invention, it provides an analysis chip, which comprises one or more reactors with minimal height,~~

~~wherein said reactor comprises The fourth embodiment of the present invention provides an analysis chip, which comprises one or more open non-flow reactors with minimal height, wherein said reactor comprises at least probe-ligand, substrate probe region, open partition-structure with minimal height, and optionally, reactor-protecting structure,~~

~~wherein said open partition-structure comprises:~~

- ~~1). substrate blank region with a width of 0.5-10mm; and optionally,~~
- ~~2). highly hydrophobic convex or/and water absorbing convex, all of which presents a height less than 1000 μ m, optimally less than 500 μ m relative to said substrate probe region,~~

SUBSTITUTE SPECIFICATION (marked up)

wherein:

(1). said substrate blank region and substrate probe region are on the same plane of a same substrate, which present a water contact angle as 40° - 80° ;

(2). said highly hydrophobic convex contains, at least in its partial surface, highly hydrophobic material, wherein said highly hydrophobic material presents a water contact angle of 40° bigger than that of said substrate probe region;

and (3). said water absorbing convex contains, at least in its partial surface, water absorbing material, wherein said water absorbing material presents a water absorptivity more than 0.1g/g.

In fact, the analysis chips include the analysis chip with highly hydrophobic partition structure, the analysis chip with water absorbing partition structure and the analysis chip with highly hydrophobic/water absorbing partition structure of the invention. The invented partition structure can be applied into all types of chips, such as the chip in which the smallest distance among reacting well is over 20% longer than the width of reacting well on its outstretched line; the chip with feeding structure or/and liquid out structure; the chip with one or more structures controlling the directional flow speed of reaction media on the feeding area or/and liquid out area of the reactor; double plane chip, and etc. The invented partition structure contains clear area(blank region on substrate with a width bigger than 0.2mm, located on the same plane of probe region on substrate, which is very important and indispensable for chips. Differing from the devices like ELISA plate immobilized with one type of probe, the reactors of the invented chip are usually immobilized with the arrays of varied types of probes therein, demanding the uniformity of the reaction circumstances for every probe in the array. But the existence of highly hydrophobic convex or water absorbing convex or highly hydrophobic/water absorbing complex convex will change the reaction conditions in its peripheral width defined districts. So, a clear area(blank area between probe region on substrate and convex is required and this area isn't immobilized with efficacious probes. Through numerous experiments, we discovered that the width of the clear area(blank area depends mainly on the height of convex and the surface static water contact angle of highly hydrophobic material or the absorptivity of water absorbing material. The convex herein can forms various geometrical figures on the surface of substrate, such as single line, multi line, strip, lattice and etc. The example for highly hydrophobic/water absorbing complex convex is: the highly hydrophobic convex in the place near to probe region on substrate; alternatively, the water absorbing convex in the place far to probe region on substrate. In this chip, said reactor is an open type reactor, in which the highly hydrophobic convex, water absorbing convex contained in the open partition structure and protection structure are the same as the descriptions above.

According to another aspect of the invention, it provides an analysis chip, which comprises one or more open non flow reactors with minimal height,

wherein said reactor comprises at least probe ligand, substrate probe region, open partition structure with minimal height, and optionally, reactor protecting structure,

SUBSTITUTE SPECIFICATION (marked up)

~~wherein said open partition structure comprises:~~

~~1). substrate blank region with a width of 0.5-10mm;~~
~~and optionally, 2). hydrophobic convex with a height less than 1000 μ , optimally less than 500 μ relative to said substrate probe region,~~

~~wherein:~~

~~(1). said substrate blank region and substrate probe region are on the same plane of a same substrate, which presents a water-absorptivity less than 0.1g/g and a water contact angle as 40-80°;~~

~~and (2). said hydrophobic convex contains, at least on its partial surface, hydrophobic material, wherein said hydrophobic material presents a water contact angle of 55-80°.~~

In fact, this the analysis-chip of the fourth embodiment is the analysis-chip with clear area ~~(the blank partition structure of the present invention. Contrary to the visions from of many people, we have found with amazement through repeated experiments, we discovered amazingly, even if there isn't that even without the partition convex, when if there is the clear area(a blank region on substrate with a whose width of is 1-10mm, under the optimal loading sample subjecting amount (e.g. 10 μ m 10 μ m is subjected on 16mm²) and reactive conditions (e.g. 30 minutes at 37 $^{\circ}$ C), no cross-contaminations occurs while in the reaction. The residual reactant can be absorbed by using water-absorbing material or pipette and or even can be washed out directly, and there is also no cross-contaminations occur contamination. In the analysis-chip with the blank partition structure of the present invention, the an optional hydrophobic convex is not the main part, but usually is employed as the marker line or/and partition auxiliary.~~

~~In this chip, said reactor is an open-type reactor, in which highly hydrophobic convex, water absorbing convex and protection structure contained in the open partition structure are the same as the descriptions above. one analysis-chip of the first embodiment or the fourth embodiment of the present invention, said hydrophobic convex includes hydrophobic coating.~~

~~According to another aspect of the invention, it provides an analysis chip, which comprises one or more flow or non flow reactors with minimal height, In one analysis-chip of the first embodiment or the fourth embodiment of the present invention, said hydrophobic coating includes colored hydrophobic line, or/and colored hydrophobic strip.~~

~~wherein said reactor comprises at least one or more striped capillary reaction chambers with a height of less than 1000 μ m, optimally 500 μ m, and optionally, reactor protecting structure;~~

~~wherein said reaction chamber comprises:~~

~~1). top plane and bottom plane with a width more than 600 μ m;~~
~~2). probe ligand and substrate probe region in which said probe ligand is immobilized;~~
~~3). closed partition structure with a height of 1-1000 μ m, optimally 1-500 μ m; and~~
~~4). inlet and outlet;~~

SUBSTITUTE SPECIFICATION (marked up)

wherein:

~~(1). said top plane and bottom plane are parts of top unit and bottom unit of said striped capillary reaction chamber, respectively;~~

~~(2). said substrate probe region is on said top plane or/and bottom plane;~~

~~(3). said closed partition structure is placed between said top plane and bottom plane;~~

~~(4). material and dimension of said planes, and distance between said top plane and bottom plane are such that the capillary phenomenon of analysis media can take place in said striped capillary reaction chamber;~~

and ~~(5). said substrate probe region presents a water absorptivity less than 0.1g/g and a water contact angle as 40-80°. Actually, this type of analysis chip is the analysis chip with striped capillary reaction chamber of the invention. Said reactor is flowing or non-flowing reactor. The situation of probe immobilization includes three patterns: probe is immobilized on the substrate in bottom unit, probe is immobilized on the substrate in top unit, probes are immobilized respectively on the substrate in bottom unit and top unit. The positions of liquid inlet and outlet at least includes three patterns too: they are on bottom unit, on top unit, and in between bottom unit and top unit. The differences of the analysis chip with striped capillary reaction chamber in the invention from present closed flowing chip, microchannel chip, and capillary chip can be referred to the differences between striped capillary reaction chamber in this invention mentioned above and the reactors of present chips.~~

~~In this chip, the striped capillary reaction chamber and protection structure are the same as the descriptions above.~~

~~According to another aspect of the invention, it~~ The fifth embodiment of the present invention provides an analysis-chip, which comprises one or more flow reactors with minimal-height, wherein said reactor comprises at least:

1). probe-ligand,;

2). substrate probe region with a water-absorptivity less than 0.1g/g and a water contact angle as 40-80°;

3). convex flow-path comprising high-hydrophilic convex with a width of 5-4000µm and a height of 0.05-1000µm, optimally 0.05-500µm relative to said substrate probe region;

and optionally,

4). reactor-protecting structure,

wherein said high-hydrophilic convex contains, at least in its partial surface, highly-hydrophilic material, wherein said highly-hydrophilic material presents a water contact angle less than 40°. In one of the analysis-chip of the present invention, said highly-hydrophilic material presents a water contact angle less than 30°. Said highly-hydrophilic materials include highly-hydrophilic nanometer material (e.g. highly-hydrophilic nanometer material) and highly-hydrophilic polymer material (e.g. highly-hydrophilic polyacrylate acid paint).

In fact, the analysis-chip of the fifth embodiment ~~Actually, this analysis chip is the analysis-chip with convex flow-path in of the present invention, whose convex~~

SUBSTITUTE SPECIFICATION (marked up)

~~flow-path that~~ can be connected to one or more of the following structures: sample well, reagent well, test well, waste liquid well, separator and etc. Said reactor is ~~flowing or non-flowing reactor. The differences of the invented analysis chip with convex flow-path from present microchannel analysis chip can be referred to those between the invented convex flow-path described above and present microchannel. Similarly, its convex flow-path and protection structure are the same as the descriptions above.~~ a flow or non-flow reactor. The convex flow-path of the invented chip differs particularly from the micro-channel path of present chips. The flow-path of the latter needs to make channels, troughs or capping, and is a concave flow-path, whose manufacturing is complicated and the cost is expensive.

~~In this chip, said reactor is an open reactor. The reactor includes~~ In one analysis-chip of the first embodiment or the fifth embodiment of the present invention, said convex flow-path refers to a coating with said highly-hydrophilic material.

In one analysis-chip of the first embodiment or the fifth embodiment of the present invention, said convex flow-path comprises hydrophobic convex or/and highly-hydrophobic convex as its partition structure, wherein said convex presents a height less than 1000 μ m, optimally less than 500 μ m.

In one analysis-chip of the first embodiment or the fifth embodiment of the present invention, said convex flow-path comprises immobilized separating-media, including electrophoresis media or chromatography media.

In one analysis-chip of the first embodiment or the fifth embodiment of the present invention, said reactor comprises also the open partition structure mentioned above in the first embodiment of the present invention.

~~According to another aspect of the invention, it~~ The sixth embodiment of the present invention provides an analysis-chip, which comprises one or more open reactors with minimal-height,

wherein said reactor comprises at least probe-ligand, substrate probe region, marking-system convex, and optionally, reactor-protecting structure,

wherein said marking-system convex refers to marker-containing convex that does not cover said probe-ligand. ~~Actually, this analysis chip is the analysis chip with immobilized marker in the invention. In the chip, said reactor is an open reactor. And its convex of marking system and protection structure are the same as the descriptions above.~~

~~One of the invented analysis chip, which comprises one or more reactors with minimal height,~~

~~wherein said reactor comprises:~~

- ~~1). easily detachable substrate easily dismantled if needed, or/and~~
- ~~2). reactor-protecting structure with minimal height, comprising protective unit,~~

~~wherein:~~

- ~~i). Said height, a distance from substrate probe region to bottom plane of said protective unit is~~

SUBSTITUTE SPECIFICATION (marked up)

In fact, the analysis-chip of the sixth embodiment is the analysis-chip with fixed marker. This invented convex of marking system can be in various geometric figures, such as dots, lines, strips, spheres etc.

In one analysis-chip of the first embodiment or the sixth embodiment of the present invention, said marking-system convex refers to convex of controlled marker-releasing system, wherein said controlled marker-releasing system comprises marker and presents a half-releasing-period of said marker of more than 10 seconds, optimally more than 30 seconds, wherein said marker comprises labeling reagent and marking-ligand, wherein:

1). said labeling reagent includes one or more of the following reagents: enzyme, fluorescent dyestuff, chemiluminescent catalyst, nonferrous metal or nonferrous metallic salt, dyestuff and paint; and

2). said ligand includes one or more of the following substances: antigen, antibody, biotin, drug ligand polypeptides, DNA, RNA and the fragments thereof.

One example of said controlled marker-releasing system is the programmable release system, in which the release velocity and the lag-time of marker are defined mainly by the selected material and structure of the system itself. For the marker in said convex of marking system, the labeling methods include chemiluminescent labeling, excitation luminescent labeling, non-selective light reflection labeling and selective light reflection labeling.

In the present invention, the term "half-releasing-period" refers to the time needed to release 50% of markers from controlled marker-releasing system into the reactor under the condition of labeling reaction. The convex with controlled marker-releasing system can be of various technical designs. For instance, it can be made controlled-releasing agent in the shape of a sphere or other solid figures containing liquid or solid markers; or a dot or line etc., which contains markers and controlled-releasing agent. In these cases, the marking convex has a height less than 1000 μ m, which is fixed on the periphery of or inside probe array in the reactor to form probe/markings system arrays.

In one analysis-chip of the first embodiment or the sixth embodiment of the present invention, said controlled marker-releasing system comprises said marker and controlled-releasing agent. In the present invention, the term "controlled-releasing agent" refers to the agent that can control or take part in controlling the releasing speed of the marker and delay the releasing. Some examples of the controlled-releasing agent are: the diffusion-controlling agent that controls the marker releasing through controlling the change of the network density; the chemical reaction-controlling agent that controls the marker releasing through controlling degradation; solvent activation-controlled release agent that controls the marker releasing through controlling the activation process (e.g. dissolving); the controlled-releasing agent that speeds up release though using water-absorbing and swelling materials inside the membrane to make the membrane dilate and disintegrate etc. With the diffusion-controlling system, the marker is released according to the fluctuation of density of diffusion-controlling agent (e.g. polymer with moderate solvency and dilatibility) in the network; with chemical reaction-controlling system, the marker is released when

SUBSTITUTE SPECIFICATION (marked up)

the controlling agent (e.g. degradable polymer) is degraded; with the activation-controlling system, the marker is released when the controlling agent (e.g. membrane) is activated (e.g. dissolved) by solvent. For example, in the diffusion-controlling system with markers evenly dispersed or embedded in polymer that has moderate water-solubility (controlled-releasing agent), the releasing speed of the marker is decided by the dissolving and swelling speed of the polymer, thereby the marker concentration can be adjusted to accommodate the requirements of different testing procedures. Taking another example with the chemical reaction-controlling system in which the marker is evenly dispersed or embedded in the degradable polymer (controlled-releasing agent), the marker-releasing velocity is actually zero when sample is subjected. While labeling, the marker is released due to the degradation of polymer with the help of degrading agent (e.g. enzyme). For still another example, in the activation-controlling system made up of markers and membrane (controlled-releasing agent), the release or delayed release of the marker is decided by the speed of membrane dissolution and dilation.

In one analysis-chip of the first embodiment or the sixth embodiment of the present invention, said marking convex presents a height less than 1000 μ m, and is fixed around the array of said probe-ligand in said reactor or inside the array of said probe-ligand to form an array of probe-ligand and marking system.

In one analysis-chip of the first embodiment or the sixth embodiment of the present invention, said convex of controlled marker-releasing system includes mono-sandwiched or multi-sandwiched structure made up of said marker and controlled-releasing agent, wherein said sandwiched structure refers to structure where the concentration of said marker is higher inside than outside. In multi-sandwiched structure, one or more types of markers and one or more types of controlled-releasing agents could be included. For example, the first layer may comprise the marker; the second layer may comprise the structure of enhancing agent. Said release-controlling agent includes water-soluble organic compounds or organic compounds, which will disintegrate in water solution. The former includes natural water-soluble organics, partially synthetic water-soluble organics and synthetic water-soluble organic compound etc. Said organic compounds include one or more of the following materials: carbohydrates and the derivatives thereof, plant starch and modified starch, plant gum, animal gum, modified cellulose, polymer and condensate.

In one analysis-chip of the first embodiment or the sixth embodiment of the present invention, said controlled-releasing agent includes water-soluble organic compound or organic compound which will disintegrate in water solution.

In one analysis-chip of the first embodiment or the sixth embodiment of the present invention, said organic compound includes one or more of the following materials: carbohydrate and its derivatives thereof, plant starch and modified starch, plant glue, animal glue, modified cellulose, polymer and condensate.

In one analysis-chip of anyone of above embodiments of the present invention, said reactor-protecting structure comprises protective unit with a distance less than 1000 μ m, optimally less than 500 μ m from said substrate probe-region; wherein;

and ii): said protective unit closes at least partially said reactor structure when no

SUBSTITUTE SPECIFICATION (marked up)

sample is subjected, and it is irreversibly removed completely or partially when sample is to be subjected.

~~Actually, this analysis chip is an analysis chip for selective use in this invention, which includes two kinds: the detachable chip and the openable~~ The seventh embodiment of the present invention provides an analysis-chip, which comprises one or more reactors with minimal height, wherein said reactor comprises: 1). easily-detachable substrate easily dismantled if needed, or/and 2). reactor-protecting structure with minimal-height, comprising protective unit, wherein: i). said height, a distance from substrate probe-region to bottom plane of said protective unit is less than 1000 μ m, optimally less than 500 μ m; and ii). said protective unit closes at least partially said reactor structure when no sample is subjected, and it is irreversibly removed completely or partially when sample is to be subjected.

In fact, the analysis-chip of the seventh embodiment refers to the optionally-using analysis-chip of the present invention, in which a part of reactors are used for the analysis while other reactors of the chip rest in protected situation. The optionally-using analysis-chip includes two types: the detachable analysis-chip and openable analysis-chip. In the former, substrate of the chip can be easily dismantled (so that only a part of the substrate with a part of the reactors are used, e.g. the activated glass, metal, metals, plastic plate and plates etc. which that have undergone the processes of pre-cutting lines on it). In the latter, reactor is reactors are covered by sealing unit enclosing units (e.g. the plastic plate with a removeable removable area made by mechanic cutting, aluminous plastic film, and plastic film with or without removeable parts, etc.). The protecting structure of the chip is the same as what is described above-removable parts, etc.).

The In one analysis-chip of the first embodiment or the seventh embodiment of the present invention, said protecting unit includes one or more of the followings: organic film or/and plate, film or/and plate of metal-organic complex, and slide.

In one analysis-chip of the first embodiment or the seventh embodiment of the present invention, said protecting unit is connected with the reactor through one or more of the following reversible/ irreversible enclosing structures: thermal enclosing structure, chemical enclosing structure and reversible or irreversible adhesive layer.

In one analysis-chip of the first embodiment or the seventh embodiment of the present invention, said protecting unit is precut for the convenience of possible removal.

The eighth embodiment of the present invention provides an analysis-chip with a high density of reactors, wherein:

- 1). said density of reactors is more than 2 reactors/cm², optimally more than 3 reactors/cm² on at least one plane of a substrate; and
- 2). said reactor comprises partition structure with a height less than 1000 μ m, optimally less than 500 μ m.

~~As one of designs for the invented chips, said reactor~~ In one analysis-chip of the eighth embodiment of the present invention, said density is more than 5 reactors/cm².

SUBSTITUTE SPECIFICATION (marked up)

~~As one of designs for the invented chips, said reactor is any reactor in claim 1-30, which has a partition structure at a minimal height. In one analysis-chip of the eighth embodiment of the present invention, said reactor refers to said reactor with minimal-height, which is that mentioned in anyone of analysis-chip of above embodiments of the present invention.~~

~~This~~ The present invention also involves ~~top unit or bottom unit used in above chips. The top unit or bottom unit includes the probe region on substrate and the~~ the top or bottom units used in the analysis-chip of the first or second embodiments. The top or bottom units include the substrate probe region and immobilized probe therein, such as the top unit or bottom unit for generating units that form the striped-capillary reaction-chamber. Said units contain the substrate probe region on substrate and probe, and partial part or whole chamber walls, partial wall, part or whole liquid-inlet and liquid-outlet, partial part or whole enclosing structure (e.g. elastic coating and wetness-proof coating), and as well as other structures of the analysis-chip (e.g. the fixing structure). The material of the top unit is selected from one or optional two or more than two of the following materials or their combinations below: glass, silicon, metal oxide, metal metals and polymer material and as well as their respective derivatives.

~~This~~ The ninth embodiment of the present invention also ~~involves~~ provides a base-plate used for the analysis-chips of the present invention, comprising:

- 1). more than one of substrate probe regions; and
- 2). one or more of the following reactor structures: (1). the convex flow-path by Claim 1 or any claim from 22 to 26; or (2). the open partition structure by Claim 1 or any claim from 10 to 16. ~~According to another aspect of the invention, it is to provide a qualitative or/and quantitative analysis method, comprising:~~

~~(a) subjecting the sample into the open reactor in an analysis-chip and making the reaction therein; and~~

~~(b) after the reaction is completed, the residual sample needn't cleaned out from the reactor and the followed procedures are carried on directly, said followed procedures include washing or labeling. In this method, the open chip is the open multi-reactors-chip described above.~~

~~According to another aspect of the invention, it~~ The tenth embodiment of the present invention provides a qualitative or/and quantitative analysis method, including:

~~(a) 1). subjecting the sample into the reactor of said analysis-chip and taking probe-selective reaction and labeling reaction therein at the same time; marking reaction respectively, wherein said analysis-chip is any analysis-chip of the present invention (from the first embodiment to eighth embodiment); and~~

~~(b) 2). washing the reactor and analyzing the result of the reaction.~~

~~In this method, the chip is the chip described above.~~

SUBSTITUTE SPECIFICATION (marked up)

~~According to another aspect of the invention, it provides a device for detection, said device comprising the pieces~~ The eleventh embodiment of the present invention provides a test device, which comprises cleaning unit, wherein said cleaning unit is used for cleaning up the residual in the analysis-chip reactor after the when reaction is finished, wherein said pieces performing said cleaning is performed though absorption with water-absorbing material, or/and through washing directly on the chip with an included angle with horizontal plane, in said cleaning unit, wherein said water-absorbing material presents a water-absorptivity larger than 0.5g/g; said included angle is bigger than 5°.

The advantages of the ~~invented highly integrated analysis-chip of the first embodiment of the present invention~~ are: simple and easy preparation, lower cost, reliable reactor-partition, even homogenous distribution of reaction media, small consumption of reaction media, high sensitivity, convenient performance and etc.

The advantages of the analysis-chip of the second embodiment of the present invention (the analysis-chip with striped capillary reaction-chamber) ~~invented analysis-chip with highly hydrophobic partition structure, analysis-chip with water-absorbing partition structure, analysis-chip with highly hydrophobic/water absorbing complex partition structure, analysis-chip with clear area as partition structure~~ are: the minimization of the height of partition structure enables the maximization of reactor numbers or/and the minimization of sample volume or/and easy washing; and laser confocal scanner or laser scanner can be used directly for scanning.

The advantages of the ~~invented chip with striped capillary reaction-chamber~~ are: it overcomes not only the disadvantages of the chip with the closed-chamber, such as inequable unequal distribution of media (e.g. the appearance existence of air bubble) and on the chip, as well as the requirement of more sample and marker needed, but also the defects of complicity in capillary analysis-chip with complicated manufacture and high cost; ~~so~~; hence it has possesses the advantages of simple and easy manufacturing, high sensitivity, less consumed consumption of reaction media, convenient performance and etc.

The advantages of the ~~invented analysis-chip of the third or fourth embodiment of the present invention (the analysis-chip with highly-hydrophobic partition structure, the analysis-chip with water-absorbing partition structure, the analysis-chip with highly-hydrophobic/water-absorbing complex partition structure, the analysis-chip with the blank region)~~ are: the minimal height of the partition structure brings about the maximization of reactor numbers, the minimization of subjected-sample volume, or/and convenience in washing; moreover the laser confocal scanner or laser scanner can be used directly for scanning.

The advantages of the analysis-chip of the fifth embodiment of the present invention (the analysis-chip with convex flow-path) are: the flowing flow speed can be controlled by selecting different convex material ~~of convex~~; the preparation is simple and the cost is low.

The advantages of the ~~invented chip with immobilized marker~~ analysis-chip of the sixth embodiment of the present invention (the analysis-chip with fixed marker) are:

SUBSTITUTE SPECIFICATION (marked up)

with the controlled marker-releasing system, Hook ~~effect~~ Effect can be reduced; therefore the sensitivities of test and device are improved; by simplifying the operation procedures and mechanical transporting system, the efficiencies of test and test device are raised, and automatic test is made ~~available~~; possible; under the dried condition, marker will have much higher stability.

The advantages of ~~analysis-chip for selective use in this invention are: In one test, only some reactors on the~~ the analysis-chip of the seventh embodiment of the present invention (optionally-using analysis-chip) in the present invention are: only part of reactors on the analysis-chip will be involved as required in accordance with the need, while others can be well preserved; thereby cost is reduced.

~~Illustrations~~ BRIEF DESCRIPTION OF THE DRAWINGS

Picture FIG. 1A is the schematic diagram of the invented analysis-chip with multiple striped-capillary reaction-chambers;

Picture FIG. 1B is the sectional drawing (along a – a line) of the analysis-chip showed in Picture FIG. 1A;

Picture FIG. 2A -2E are the schematic diagram of different types of reactors and structures of the invented chips;

Picture FIG. 3A -3B are the vertical view (downwards) of the bottom unit of the enclosing structure of the invented striped-capillary reaction-chambers;

Picture FIG. 3C and 3D are the vertical view (upwards) of the top unit.

1. Striped-capillary reaction-chamber
2. Reactor structure
3. Convex of marking system
4. Open partition structure
5. Top plane
6. Bottom plane
7. Substrate probe region
8. Closed partition structure
9. Inlet
10. Outlet
11. Top unit
12. Bottom unit
13. Inlet structure on the top plane
14. Outlet structure on the top plane
15. Fixing structure on the top plane
16. Seal structure on the top plane

~~Detailed description~~ Implementation methods

Definition of terms

In ~~this~~ the present invention, the term “analysis-chip” or “chip” in short, refers to a test device for qualitative and/or quantitative analysis, wherein the result of the specific reaction between a small amount of probe-ligand and the target molecule in a

SUBSTITUTE SPECIFICATION (marked up)

sample can be identified in an addressable way. Analysis-chip includes, but not only includes, the "biochip", "microarray", "bioarray". The analysis-chip includes micro-channeled analysis-chip (e.g. micro-channeled biochip) and microarray analysis-chip (e.g. biochip, microarray, bioarray etc.), but as known to all it doesn't include the available rapid test strip. The analysis-chip in ~~this~~ the present invention contains a mono-reactor or multi-reactors with or without the marking system, in which the probe-ligand is immobilized on a substrate with a probe-spot density more than 10 spots/cm² and a probe-spot covering area not larger than 1mm²/spot.

In ~~this~~ the present invention, the term "test device" ~~in this invention~~ refers to articles used in the quantitative or/and qualitative analysis, which contain probe-ligand reacting with the target in a sample, e.g. instrument and consumable which contain probe-ligand, and kit containing probe-ligand and marking-ligand. Some examples of the test device are: analysis-chip, ELISA plate, affinity electrophoresis strip, affinity chromatography column, planar chromatography reagent strip, analysis-chip kit, ELISA plate kit, affinity electrophoresis kit, etc. The quantitative or/and qualitative analysis can be performed either in vitro, or in vivo.

In ~~this~~ the present invention, the term "probe-ligand" refers to all active materials that can be immobilized on a solid support in an addressable way so that the target in a sample can be captured by probe-ligand, e.g. DNA, polypeptides, cells, tissues and bio-components etc.

In ~~this~~ the present invention, the term "ligand" refers to the material that is used to: 1) capture its ligate through interaction (including affinity effect, ion exchange, oleophilic effect, etc.), and 2). bind with labeling material to generate marker. For example, it includes one or more of the following materials: antigens, antibodies, ligates, aptamer screened by Systematic Evolution of Ligands by Exponential Enrichment (SELEX), ligands, polypeptides, polysaccharides, coenzyme, cofactors, antibiotics, steroid, viruses, cells, biotin, avidin etc.

In ~~this~~ the present invention, the term "labeling material" refers to materials generating or taking part in the formation of the detection signal, such as Rhodamin, Cy3, Cy5 etc, which are commonly used in the analysis-chip detection.

In ~~this~~ the present invention, the term "substrate" refers to solid support where probe in an analysis-chip are immobilized.

In ~~this~~ the present invention, the term "reaction room" refers to the place in a reactor where probe-ligand and target react with each other. The reaction room includes the reaction well and reaction-chamber. The reaction well is an open reaction room in which the probe array is open during the reaction. The reaction-chamber is an closed reaction room in which the probe array is closed in its above part during the reaction. The reaction well includes the substrate well and probe. The reaction-chamber includes the substrate chamber and probe. The substrate well and substrate chamber all include substrates and reactor partition structures.

In ~~this~~ the present invention, the term "reactor" refers to the whole system consisting of the reaction room and all the connected structures therein. A reactor includes the borderline or partition structure, substrate, probe immobilized on the substrate and other connected structures (e.g. flow-path, inlet structure, outlet

SUBSTITUTE SPECIFICATION (marked up)

structure, the fixed marker, etc.). In ~~this~~ the present invention, the biochip is defined as mono-reactor biochip ($N=1$) and multi-reactor biochip ($N=2$ or >2) according to reactor number N presented by the chip. The reactor is defined as a flow reactor and a non-flow reactor depending whether the added liquid media can flow directionally in the reactor during the detection. The biochip characterized by the flow reactor and non-flow reactor is defined as a flow analysis-chip and a non-flow analysis-chip respectively. The reactor is defined as the open reactor and non-open reactor respectively depending whether the probe array in the reactor is open in the whole course of detection. Accordingly the biochip characterized by these reactors is defined as the open analysis-chip or non-open chip, respectively. The reactor of said analysis-chip can simultaneously be featured with several types of reactors mentioned-above. In ~~this~~ the present invention, this kind of reactor is defined according to all the properties it possesses. The analysis-chip characterized by this type of reactor is defined in the same way. For example: when a probe array is open with no covering from above during the detection, and liquid media added flow directionally in the reactor, this reactor is defined as an open flow reactor; the corresponding analysis-chip is defined as an open flow biochip; others are analogous of this.

In ~~this~~ the present invention, the term "base-plate" refers to the intermediate used for the preparation of chip, which hasn't been set with the probe. It is based on the substrate and combined with or without other structures (e.g. the partition structure). It will form an analysis-chip after being fixed with the probe-ligand. There may be one or more substrate regions on a base-plate. A single base-plate refers to the one without the partition structure. In such a case, a base-plate is just a substrate, (for example the amino glass slide available in market). A base-plate with partition structure is referred to as the base-plate with more than one of substrate probe regions. In such a case, a base-plate is composed of the substrate and partition structure. Once the probe-ligand is immobilized in a substrate ligand region, a reactor is formed. The base-plate with multiple substrate probe regions thus can form an analysis-chip with multi-reactors.

In ~~this~~ the present invention, the term "reactor structure" refers to any indispensable structure for a reactor besides the substrate and probe, such as the partition structure, flow-path structure etc.

In ~~this~~ the present invention, the term "convex" refers to a protruding structure whose height is more than 0 in relation to the plane of the substrate probe region, e.g.

In ~~this~~ the present invention, the term "reactor partition structure" refers to the structure that coating, adherend etc. can prevent cross-contamination among reactors at least in the course of sample subjection. It includes the structures used to segregate part or all of the reactor structures (e.g. reaction well, reaction-chamber, flow-path, inlet structure, outlet structure, etc.). The reactor partition structure includes open and closed partition structures. The open partition structure refers to the reactor partition structure without a cover when the analysis-chip is in use. Conversely, the closed partition structure refers to the reactor partition structure with a cover when the analysis-chip is in use.

In ~~this~~ the present invention, the term "reactor flow-path" refers to the flow-path

SUBSTITUTE SPECIFICATION (marked up)

network in the reactor. The convex flow-path of the chips of ~~this~~ the present invention refers to the flow-path higher than the substrate plane, which contains water-absorbing or/and highly-hydrophilic material.

In ~~this~~ the present invention, the term "reactor separation structure" refers to the structure in the reactor of chip, which presents sample-separation function.

In ~~this~~ the present invention, the term "marking system" refers to a system in the analysis-chip (including analysis-chip device and analysis-chip kit), which is used for marking the reaction in the reactor of the chip.

In ~~this~~ the present invention, the term "reactor protecting system" refers to a system that maintains the reactor activity in storage and transporting process, and also keeps the unemployed reactors from being contacted by reaction media when other reactors are in use. The reactor protecting structure is different from the reactor partition structure.

In ~~this~~ the present invention, the term "polypeptide" includes natural or synthetic proteins, protein fragments, synthetic peptides, etc. Polypeptide includes the common targets in immunoassay and the popular ligands in detection, e.g. antigens, antibodies, etc.

In ~~this~~ the present invention, the term "nano-particle" refers to solid support particle with a size of less than 500nm, optimally 1-100nm, at least in one-dimension of its three-dimensions.

In ~~this~~ the present invention, the term "chip with convex flow-path" refers to an analysis-chip comprising convex flow-path; the term "analysis-chip with highly-hydrophobic partition structure" refers to an analysis-chip containing the partition structure with the highly-hydrophobic convex; the term "analysis-chip with water-absorbing partition structure" refers to an analysis-chip containing the partition structure with the water-absorbing convex; the term "analysis-chip with blank-region partition structure" refers to an analysis-chip containing the partition structure with substrate blank region of width is 0.5-10mm, and optionally, hydrophobic convex; the term "analysis-chip with highly-hydrophobic/ water-absorbing partition structure" refers to an analysis-chip containing the partition structure with the highly-hydrophobic convex and the water-absorbing convex; the term "analysis-chip with fixed marker" refers to an analysis-chip containing fixed marker; the term "optionally-using analysis-chip" in the invention refers to an analysis-chip with multi-reactors, where only part of reactors are to be involved in the testing if needed, without interfering with other reactors. ~~Term "analysis-chip with highly hydrophobic partition structure" in the invention refers to the chip containing the partition structure with highly hydrophobic convex.~~

~~Term "analysis-chip with water-absorbing partition structure" in the invention refers to the chip containing the partition structure with water-absorbing convex.~~

~~Term "analysis-chip with clear area as partition structure" in the invention refers to the chip containing the partition structure including clear area on substrate with a width of 0.5-10mm and optionally hydrophobic convex.~~

~~Term "analysis-chip with highly hydrophobic or/and water-absorbing complex partition structure" in the invention refers to the chip containing the partition structure~~

SUBSTITUTE SPECIFICATION (marked up)

~~with highly hydrophobic or/and water absorbing complex convex.~~

~~Term "analysis chip with immobilized marker" in the invention refers to the chip containing immobilized marker.~~

~~Term "analysis chip for selective use" in the invention refers to the chip with multi-reactors, where only part of reactors can be involved in the testing if needed, without interfering with other reactors.~~

~~In this~~ In the present invention, the term "water contact angle" refers to the water contact angle on a surface. For a long time, it has been widely acknowledged that contact angle~~of~~ liquid drop on the surface of a solid substance can be taken as the quantitative indicator of some specific moisture capacity. If liquid is dispersed entirely on the surface and forms a membrane, then the contact angle~~is~~ zero. If certain angle is formed between the drop of liquid and the surface of substance, the surface is not considered wet. Glass is the most commonly used material as the substrate of solid support of chips, whose water contact angle is about 45°.

With the following ~~implementation examples~~ embodiments, more detailed explanations of the invention will be given. However, it should be pointed out that these examples are only the individual cases concerning the implementation of ~~this~~ the present invention. Professionals should learn more about other aspects of the implementation based on these examples.

The substrate in the ~~implementation example of this~~ embodiment of the present invention includes hydrophilic substrate and hydrophobic substrate. The former includes the epoxy glass slide and epoxy-group cover glass made by epoxidation. The latter is the glass slide painted black made by ~~ourselves~~ us. The glass slides are purchased from USA ESCO SCIENTIFIC Comp. The dimension is 76×26×1.0mm; the cover glass is 60×24×0.15mm. The probes purchased from Hepatic Disease Institute, Beijing People Hospital are HIV1+2 antigens, HBs antigens, HCV antigens, HBs antibodies respectively. The spotting concentration is within 1.0-1.5mg/ml. In the ~~implementation examples~~ embodiments, Sample 1 is HCV antibody-positive serum. Sample 2 is HIV1+2 antibody-positive human serum. Sample 3 is HBs antibody-positive human serum. Sample 4 is HBs antigen-positive human serum. Sample 5 is a negative control. All the samples are predetermined under the same testing condition by the classic open analysis-chip with the mono-reactor.

Implementation example 1: Preparation of the analysis-chip with the highly-hydrophobic partition structure as well as the application thereof

In this ~~implementation example~~, the embodiment, the liquid highly-hydrophobic liquid materials in use ~~is~~ are "polyacrylate paint" (made by China Chengdu Chenguang Research Institute of Chemical Industry, with a water contact angle as 85°), "organosilicon water-proof paint" (made by China Chengdu Chenguang Research Institute of Chemical Industry, with a water contact angle as 116°), "highly-hydrophobic latex paint" (supplied by China Chengdu Chenguang Research Institute of Chemical Industry, with a water contact angle as 123°), "highly-hydrophobic silica paint" (supplied by China Zhoushan Mingri Nanomaterials Co., Ltd., with a water

SUBSTITUTE SPECIFICATION (marked up)

contact angle as 151°) respectively. The solid highly-hydrophobic ~~solid substances~~ materials in use herein are “polytetrafluoroethylene pressure-sensitive adhesive tape” (supplied by China Chengdu Chenguang Research Institute of Chemical Industry, with a water contact angle as 117°), and “nanometer textile” (supplied by China Zhoushan Mingri Nanomaterials Co., Ltd., with a water contact angle as 155°) respectively. Although the reactor partition structure of the invented ~~reactor chip~~ could partially or entirely be the device of this the present invention, this ~~implementation~~ example embodiment only takes the simplest cases. Other cases may be illustrated in the following ~~implementation examples~~ embodiments.

1) The preparation of the substrate with highly-hydrophobic partition structure

(1) Preparation of the substrate with highly-hydrophobic partition structure by solidifying the highly-hydrophobic liquid material. Coat said liquid highly-hydrophobic ~~liquid~~ materials onto the ~~borderline of the reactor on~~ surface region of the epoxy-group slide, where the partition structure will be formed. In accordance with the supplier's instruction, solidify it after it is dried at room temperature, form a highly-hydrophobic convex whose height is ~~25-115μm~~ 115μm and whose width is 2.0-2.5mm, ~~and make the~~. The convex can be made into various geometric shapes. In this ~~example~~ embodiment, only two types are used: strip (the convex is in a shape of strip) and line combination (e.g. the convex has two lines with space in between). The surface enclosed by highly-hydrophobic convex could be in various geometric figures. In this ~~example~~ embodiment, 3mm×3mm rectangle is used. On the surface of the substrate, there are 20 substrate-wells altogether, 10 substrate-wells being arranged lengthwise and 2 substrate-wells transversely.

(2) Preparation of the substrate with highly-hydrophobic partition structure by ~~immobilizing~~ fixing the solid highly-hydrophobic ~~solid~~ materials

Adhere the highly-hydrophobic solid material onto the ~~borderline of the reactor on the epoxy glass slide to form~~ surface region of the epoxy-group slide, where the partition structure will be formed. So, a highly-hydrophobic convex is formed on the substrate, whose height is 105-435μm, and whose width is 2.0-2.5mm. The surface enclosed by the highly-hydrophobic convex could be in various geometric shapes. In this ~~example~~ embodiment, the surface enclosed by highly-hydrophobic convex is a 3mm×3mm rectangle. On the surface with highly-hydrophobic convex of the substrate, there are 56 substrate-wells altogether, 14 substrate-wells being arranged lengthwise, and 4 substrate-wells transversely.

2) The preparation of the analysis-chip with ~~the~~ highly-hydrophobic partition structure

In fact, the invented analysis-chip can be ~~fixed with probes first and then go on with the preparation~~ prepared by two methods: (1). The probe immobilization before the formation of the highly-hydrophobic convex; or the other way around: preparing and (2). The probe immobilization after the formation of the highly-hydrophobic convex first and then fixing the probe later. This example. This embodiment adopts the second method. In the probe region 0.5mm away from said highly-hydrophobic convex in the substrate-well, 3 types of antigens mentioned-above are immobilized by

SUBSTITUTE SPECIFICATION (marked up)

the known method of probe spotting. A 3×3 probe array thus comes into being, with each antigen for 3 spots. Then block the analysis-chip with bovine serum albumin. The final structure of reactor (Fig 2A) includes the probe region on substrate and open partition structure.

3) Evaluation and applications of the analysis-chip with the highly-hydrophobic partition structure

In the experiment, take 10 chips of each type mentioned-above, number the reaction wells, any of the two reaction wells border upon are added respectively the positive serum of the mixture of the same volumes of Sample 1, 2, 3 and the negative control serum. The marker used is the mouse monoclonal antibody labeled with Rhodamine, which is self-made with the known method. In the experiment, the sample subjecting volume is 10μl; the marker subjecting volume is 10μl. When the sample is added and after the reaction is completed, there is no need to suck all the unbound substance in the reaction wells before washing as performed in ELISA. Instead, washing is conducted in accordance with one of the following approaches: (a) suck the unbound substances in the reaction well slightly with absorbent paper. And then rinse it for 1 minute with wash solution; (b) rotate the slide to form an angle of 45° with the horizontal plane, and then rinse it for 1 minute by spraying washing solution downward; (c) rotate the slide to form an angle of 180° with the horizontal plane, and then rinse it for 1 minute by spraying washing solution upward. The marker is added, washed, and dried with the known methods. After being dried, it is scanned with scanners. The scanner used herein is a laser confocal scanner (Afymetrix, GMS 418 microarray scanner), with wavelengths of excitation light at 532nm; emission light at 570nm. The visualized signal is processed by software (JAGUAR□ s). The cross-contamination rate is defined as follows: the numbers of reaction wells, in which the acquired results disagree with the added samples, is divided by total numbers of reaction wells examined. The experimental results are showed in Table 2:

Table 2

Chip	Highly-hydrophobic material	Substrate	The thickness of convex	Convex structure	Blank space	Cross-Contamination rate
1	Polyacrylate paint	Epoxy slide	75-105μm	Strip	>500μm	0
2	Organosilicon water-proof paint	Epoxy slide	20-115μm	Strip	>500μm	0
3	Organosilicon water-proof paint	Epoxy slide	20-89μm	Strip	>500μm	0
4	Organosilicon water-proof	Epoxy slide	15-106μm	The line combination	>500μm	0

SUBSTITUTE SPECIFICATION (marked up)

	paint			of		
5	Highly-highly-hydrophobic latex paint	Epoxy slide	75-105 μ m	Strip	>500 μ m	0
6	Highly-hydrophobic silica paint	Epoxy slide	65-89 μ m	Strip	>500 μ m	0
7	Polytetrafluoroethylene pressure-sensitive adhesive tape	Epoxy slide	120 μ m	Strip	>500 μ m	0
8	Nanometer textile	Epoxy slide	400 μ m	Strip	>500 μ m	0
9	Nanometer textile	Black paint slide	400 μ m	Strip	>500 μ m	0

Implementation example 2: Preparation of the analysis-chip with the water-absorbing partition structure and applications thereof

In this example embodiment, the water-absorbing materials in use are: “starch grafting acrylic acid water-absorbing membrane (whose thickness is 80-100 μ m, water absorbability 450g/g, provided by Chenguang Research Institute of Chemical Industry)”, “water-absorbing paper (whose thickness is 80-100 μ m, water absorbability 150g/g, provided by Chenguang Research Institute of Chemical Industry)” and deacetylated chitin grafting acrylonitrile water-absorbing membrane (whose thickness is 80-100 μ m, water absorbability 220g/g, provided by Chenguang Research Institute of Chemical Industry)” respectively. Although the partition structure of the invented reactor could be partially or entirely the device of ~~this~~ the present invention, this example embodiment only takes the simplest cases.

1) Preparation of the substrate with water-absorbing partition structure

First, punch 3mm holes in said water-absorbing ~~solid~~ material, adhere the material onto the epoxy glass slide, and then form a water-absorbing convex with 3mm upright holes whose height is 105-435 μ m 435 μ m, and the space between the two holes is 2.0-2.5mm. The convex can be in various geometric figures. In this example embodiment, only strip figure is used (convex is in a shape of a strip). On the surface of the substrate, there are 20 wells (substrate-well) altogether, 10 wells in lengthwise direction and 2 wells in transverse direction.

2) Preparation of the analysis-chip with water-absorbing partition structure

The preparation method is the same as that of analysis-chip with highly-hydrophobic partition structure in ~~Implementation example 1~~. The Embodiment 1. The block treatment of the analysis-chip is blocked performed with bovine serum albumin. Then, it is dried and is made ready for use.

3) Evaluation and applications of the analysis-chip with water-absorbing partition structure

In the experiment, take 10 chips of each type mentioned-above, number the

SUBSTITUTE SPECIFICATION (marked up)

reaction wells, any of the two reaction wells border upon are added respectively the positive serum of the mixture of the same volumes of Sample 1, 2, 3 and the negative control serum. The subjecting volume of sample is 7 μ l; that of marker is 7 μ l. The experimental method is the same as that in ~~Implementation example~~ Embodiment 1. The cross-contamination rate is defined as follows: the numbers of reaction wells, in which the acquired results disagree with the added samples, is divided by total numbers of reaction wells examined. The cross-contamination rate on the analysis-chip prepared in this ~~example~~ embodiment is zero.

Implementation example 3: Preparation of analysis-chip with a blank region as partition structure and the applications thereof

In this ~~example~~ embodiment, the hydrophobic materials in use are: "black polyacrylate paint" (supplied by China Chengdu Chenguang Research Institute of Chemical Industry, with a water contact angle as 78°), "black paint" (supplied by China Chengdu Chenguang Research Institute of Chemical Industry, with a water contact angle as 76°). The substrate used herein is the epoxy glass slide. Although the partition structure of the invented reactor could be partially or entirely the device of ~~this the present~~ invention, this ~~example~~ embodiment only takes the simplest cases.

1) Preparation of the substrate containing the marking line with a blank region as partition structure

Coat the hydrophobic paint mentioned-above on the epoxy glass slide to form a black marking line whose height is 30-40 μ m, and whose width is 500-1000 μ m. On the surface of the substrate, there are 56 substrate-wells altogether, 14 in lengthwise direction, and 4 in transverse direction.

2) The preparation of the analysis-chip with a blank region as partition structure

(1) The preparation of analysis-chip with a completely blank region as partition structure. The structure

~~The~~ partition structure with a completely blank region doesn't contain hydrophobic convex. It is made by directly immobilizing several probe arrays onto the surface of the substrate. The immobilization of each probe array in this ~~example~~ embodiment is the same as that in ~~Implementation example~~ Embodiment 1. There are 10 probe arrays immobilized lengthwise and 2 probe arrays immobilized transversely, 20 probe arrays altogether. The substrate blank region between every two probe-arrays is 4.5mm in width. The analysis-chip is blocked with bovine serum albumin and made ready for use.

(2) Preparation of the analysis-chip containing the marking line with a blank region as partition structure. Said preparation is based on the substrate prepared above, which contains the marking line with a blank region as partition structure. The preparing method is the same as that in ~~Implementation example~~ Embodiment 1.

3) Evaluation and applications of the analysis-chip with a blank region as partition structure

In the experiment, take 10 chips of each type mentioned-above, number the reaction wells, any of the two reaction wells border upon are added respectively the positive serum of the mixture of the same volumes of Sample 1, 2, 3 and the negative

SUBSTITUTE SPECIFICATION (marked up)

control serum. The subjecting volume of sample is 7 μ l; that of marker is 7 μ l. The experimental method is the same as that in ~~Implementation example~~ Embodiment 1. The cross-contamination rate is defined as follows: the numbers of reaction wells, in which the acquired results disagree with the added samples, is divided by total numbers of reaction wells examined. The cross-contamination rate on the analysis-chip prepared in this ~~example~~ embodiment is zero.

Implementation example 4: Preparation of the analysis-chip with highly-hydrophobic/water hydrophobic /water-absorbing complex partition structure and the applications thereof

In this ~~example~~ embodiment, the highly-hydrophobic liquid substance in use is "organosilicon water-proof paint" (supplied by China Chengdu Chenguang Research Institute of Chemical Industry, with a water contact angle as 116°); the water-absorbing material used herein is "starch grafting acrylic acid water-absorbing membrane (whose thickness is 80-100 μ m, water absorbability 450g/g, provided by Chenguang Research Institute of Chemical Industry)". Though the partition structure of invented reactor could be made up partially or entirely of the device of the invention, this ~~example~~ embodiment only presents the simplest cases as the samples.

1) Preparation of the substrate with water-absorbing partition structure

First, punch 3mm holes in said water-absorbing solid, painting the said highly-hydrophobic paint with 0.5-~~1.0mm~~ 1.0mm width onto the said water-absorbing solid near the each hole, ~~where~~ adhere the material onto the borderline of the reactors on the epoxy glass slide, and then form a water-absorbing convex with 3mm upright holes whose height is 105-435 μ m, and the space between the two holes is 2.0-2.5mm. The convex can be in various geometric figures. In this ~~example~~ embodiment, only strip figure is used (convex is in a shape of a strip). On the surface of the substrate, there are 20 wells (substrate-well) altogether, 10 wells in lengthwise direction, and 2 wells in transverse direction.

2) Preparation of the analysis-chip with the highly-hydrophobic/water-absorbing partition structure

The preparing method is the same as that of the analysis-chip with highly-hydrophobic partition structure in ~~Implementation example~~ Embodiment 1. The analysis-chip is blocked with bovine serum albumin, dried and then is made ready for use.

3) Evaluation and applications of the analysis-chip with the highly-hydrophobic/water hydrophobic /water-absorbing partition structure

In the experiment, take 10 chips of each type mentioned-above, number the reaction wells, any of the two reaction wells border upon are added respectively the positive serum of the mixture of the same volumes of sample 1, 2, 3 and the negative control serum. The subjecting volume of sample is 7 μ l; that of marker is 7 μ l. The experimental method is the same as that in ~~Implementation example~~ Embodiment 1. The cross-contamination rate is defined as follows: the numbers of reaction wells, in which the acquired results disagree with the added samples, is divided by total numbers of reaction wells examined. The cross-contamination rate on the analysis-

chip prepared in this ~~example~~ embodiment is zero.

Implementation example 5: Preparation of the analysis-chip with the controlled marker-releasing system and the applications thereof

The invented analysis-chip with the controlled marker-releasing system is actually an analysis-chip with a marker release-controlling system in the reactors. Similar to the drug release-controlling system, it also includes a programmable release system and an intelligent release system. The latter includes a release system with the external adjustment and intelligent gel. The marker release-controlling system of ~~this~~ the present invention can be prepared the same way as the existing drug release-controlling system.

For the programmable drug release system, the methods of dissolving system can be prepared via using the hydrogel microsphere of ortho-hydroxybenzoic acid cross-linked by Ca^{2+} ion to embed drug, ~~dusing~~ using the hollow body of polylactic acid to embed drug, ~~tusing~~ using the hollow body of polylactic acid to embed foaming agent, using microsphere of water soluble polymers such as hydroxy-propyl cellulose or hydroxy-propyl methyl cellulose to embed drug, or using the intelligent drug release system with the external adjustments (e.g. through light, heat, PH value, electromagnetic, ultrasonic wave etc.).

Though this ~~example~~ embodiment only offers the simplest cases for the preparation of the invented controlled marker-releasing system, it is clear to professionals that the method mentioned here can be used to prepare a variety of controlled marker-releasing systems.

1) The half-release period of the markers with controlled release system switched on by solvent

In this ~~example~~ embodiment, the controlled marker-releasing system is composed of the controlled-releasing agent and membrane-enclosed powder marker formed by excipient. The marker used here is enzyme-labeled goat-anti-human secondary antibody (Beijing Tiantan Biological Products Co., Ltd.). The controlled-releasing agent used herein is the water-soluble organics (see Table 3) whose coating thickness is 80-100 μm . The controlled release system is switched on by dissolution with PBS buffer solution as a solvent. First, the solution of controlled-releasing agent with proper concentration will be coated onto the slide, forming a coating of 1mm \times 1mm \times 0.1mm (length \times width \times height). After being dried, this coating is again painted with concentrated marker solution. After the marker is dried, the concentrated solution of controlled-releasing agent is coated to enclose the marker and is dried again for future use. At 37 $^{\circ}\text{C}$, a certain amount of solvent will be added to the controlled release system. The soluble parts will be taken out in different time. After that, half-release period can be calculated by detecting the dissolved marker through antibody-secondary antibody reaction. The half-release periods of marker in some controlled release systems switched on by solvent are showed in Table 3.

Table3

Controlled-releasing agent	Half-release period (minute)
----------------------------	------------------------------

SUBSTITUTE SPECIFICATION (marked up)

Starch	2
Gelatin	3
Hydroxypropyl methyl cellulose	5
Hydroxypropyl cellulose	12
Acacia	15

2) Preparation of the analysis-chip with the controlled marker-releasing system

The marker in the marking convex on said analysis-chip of this ~~example embodiment~~ is Rhodamine-labeled goat-anti-human secondary antibody. Acacia and ethyl cellulose are used as controlled-releasing agents. The substrate used herein is the substrate of analysis-chip with highly-hydrophobic partition structure based on epoxy glass slide prepared in ~~Implementation Example~~ Embodiment 1.

(1) Fixing the marking convex in the periphery of the probe array in the reactor

In ~~implementation example~~ embodiment 1, said three antigen probes are immobilized in the substrate well to form a probe array, which is then blocked with bovine serum albumin solution. Then Acacia with proper concentration is painted around bottom of the reaction well, forming a 1mm-wide strip. After being dried, the marker containing starch as excipient is coated onto the strip of Acacia, which is dried again and coated with Acacia for enclosing. After it is dried, it is made ready for use. The marking convex prepared in this way has a thickness of 350-480 μ m. Thereby in the prepared reactor structure (Fig. 2E), the marking convex 3 is outside the substrate probe region with the open partition structure around it. Of course, the marking convex can also be surrounded by the closed partition structure (Fig. 2B). And the half-release period of the marker at 37 $^{\circ}$ C is tested for 15 minutes.

(2) Fixing the marking convex inside the probe region to form the probe/marking system arrays

Following the probe-spotting method in ~~implementation example~~ embodiment 1, the marker solution containing gelatin (secondary antibody 1mg/ml) at a proper concentration and probe solutions of three antigens are spotted respectively into the substrate-well of the substrate to form the probe/marker arrays. The reactor (Fig. 2C, 2D) thus obtained has the array of probe/marking convex 3 inside the substrate probe region, surrounded with the open partition structure. The half-release period of the controlled release system at 37 $^{\circ}$ C is tested for about 3 minutes.

3) The application of the analysis-chip with the controlled marker-releasing system

In experiment, four samples are subjected into said analysis-chip with the controlled marker-releasing system respectively, with each sample in 2 reaction wells. The sample subjected should be diluted properly. In this ~~example embodiment~~, 5 μ l of samples should be subjected and kept under incubation at 37 $^{\circ}$ C for 5 minutes. After that, washing should be conducted for 3 times, with 15 μ l of washing solution added for each washing. And then, after 15 μ l of diluent is subjected, there is another 5-minute incubation at 37 $^{\circ}$ C. After reaction, it is rinsed 5 times with 15 μ l of washing solution added each time. Scanning (with GMS 418 microarray scanner made by Afymetrix,) will be conducted after drying. The processed data are listed in Table 4.

Table 4

SUBSTITUTE SPECIFICATION (marked up)

Method		Standard ELISA method	Controlled marker releasing method
HCV antibody-positive serum	HCV antibody	+	+
	HIV antibody	-	-
HIV antibody-positive serum	HCV antibody	-	-
	HIV antibody	+	+
Positive control	HCV antibody	+	+
	HIV antibody	+	+
Negative control	HCV antibody	-	-
	HIV antibody	-	-

“+” stands for the positive result; “-” the negative result.

Implementation example 6: Preparation of the analysis-chip with the convex flow-path and the applications thereof

This ~~implementation example~~ embodiment illustrates how a micro-channel path is prepared with highly-hydrophilic material. The invented analysis-chip with highly-hydrophilic micro-channel path differs from the present micro-channel path analysis-chip mainly in that the former employs the surface of highly-hydrophilic material as an important component for micro-channel path.

~~1) Preparation of the highly hydrophilic micro channel path without the partition structure~~

Though there are many highly-hydrophilic materials with varied hydrophilicities available for selection, this ~~implementation example~~ embodiment illustrates only two materials. The highly-hydrophilic liquid material used herein is “highly-hydrophilic nanometer silica paint” (provided by China Zhoushan Mingri Nanomaterials Co., Ltd., with a water contact angle as 28°) and “highly-hydrophilic polyacrylic acid paint” (supplied by China Chengdu Chenguang Research Institute of Chemical Industry, with a water contact angle as 35°).

1) Preparation of the chip with highly-hydrophilic micro-channel path which does not present micro-channel partition structure

The highly-hydrophilic liquid material is used to draw a line with a width of 80-100μm and with a length of 10mm on the surface of the slide. After being dried, it is ready for use.

2) Preparation of the chip with highly-hydrophilic micro-channel path ~~with the which presents micro-channel~~ partition structure

“Organosilicon water-proof paint” (supplied by China Chengdu Chenguang Research Institute of Chemical Industry whose water contact angle is 116°) is coated onto both sides of said highly-hydrophilic micro-channel path without the partition structure, with a width of 1mm. After being dried, the highly-hydrophilic micro-channel path with the partition structure is ready.

3) Applications of the highly-hydrophilic micro-channel path

Set said slide horizontally. Subject 10 μ l of PBS buffer solution into one end of the prepared highly-hydrophilic micro-channel path. As a result, a phenomenon similar to capillarity occurs instantly, that is, the liquid gradually flows from the liquid-subjecting end to the other end.

It is easy for professionals to apply the invented micro-channel path to the analysis-chip with micro-channel path, such as PCR chip, micro-extraction chip, chemical synthetic chip, cell counting chip, integrated analysis-chip with multi-system, bio-microarray, multi-channeled integrated chip, capillary electrophoresis chip, lab-on-chip, etc.

Implementation example 7: preparation of optionally-using analysis-chip and the applications thereof

The analysis-chip prepared in this ~~example is an~~ embodiment is the optionally-using analysis-chip, including two types: the detachable analysis-chip in which ~~the number of reactors to be used can be selected according to the analysis, includes two types: the analysis-chip in which~~ selected reactors can be detached, and the openable analysis-chip in which selected reactors can be opened, according to the need of the analysis. In the former, substrate can be easily dismantled; while in the latter, reactor is covered by sealing unit.

1) Preparation of the detachable chip

The easily-detachable substrate used in this ~~implementation example~~ embodiment is a polystyrene plate with a precut ditch that can help dismantle the substrate if needed. The area surrounded by the precut ditch is 4 \times 4 mm. The ditch is 1mm wide and 0.8mm deep. Then "Organosilicon water-proof paint" (supplied by China Chengdu Chenguang Research Institute of Chemical Industry, with a water contact angle as 116 $^{\circ}$) is painted onto the border of the area surrounded by the precut ditch, forming a highly-hydrophobic convex line with a height of 80-100 μ m and a width of about 1mm. Thereby a substrate-well comes into being. After that, said HCV fusion antigen, HIV1+2 fusion antigen, and HBs antigen are spotted respectively in 3 spots into each substrate-well, forming a 3 \times 3 arrays; while the areas on the substrate without being spotted will be blocked and dried for future use. The same preparation method is applicable to other detachable chips with an easily-detachable substrate (e.g. the activated glass slide, metal plates, plastic plates etc., which have undergone the pre-cutting).

2) Preparation of the openable chip

The reactor-sealing unit used in this ~~implementation example~~ embodiment includes: the plastic plate with a removable area made by mechanic cutting, aluminous plastic film, and plastic film with or without removable parts, etc.

Spotting is conducted in the same way as mentioned above on the substrate prepared in ~~Implementation example~~ Embodiment 3, which contains a marking line, with a blank region as the partition structure. After 20 reaction wells are formed on the substrate, waterproof pressure-sensitive adhesive with a height of 80-100 μ m, and a width of about 1mm is coated onto the border of the reactor well, which will then be

SUBSTITUTE SPECIFICATION (marked up)

enclosed by reactor-sealing units.

3) Application of the optionally-using analysis-chip

In testing, different number of reaction wells can be taken as required by dismantling parts of the substrate in the detachable analysis-chip along the precut ditch or by uncovering the easily-removable part of said openable analysis-chip with vacuum pumps, or removing the covers above the reaction well by mechanic cutting while keeping other reaction wells intact. In the experiment, take 10 chips of each type mentioned-above, number the reaction wells, any of the two reaction wells border upon are added respectively the positive serum of the mixture of the same volumes of sample 1, 2, 3 and the negative control serum. The subjecting volume of sample is 7 μ l; that of marker is 7 μ l. The experimental method is the same as that in ~~Implementation example~~ Embodiment 1. The cross-contamination rate is defined as follows: the numbers of reaction wells, in which the acquired results disagree with the added samples, is divided by total numbers of reaction wells examined. The cross-contamination rate on the analysis-chip prepared in this ~~example~~ embodiment is zero.

Implementation example 8: Application of the analysis-chip with the high - density ~~reactor~~ of reactors and the applications thereof

1) Preparation of the analysis-chip with the high -density ~~reactor~~ of reactors

In the ~~example~~ embodiment, the prepared analysis-chip with the high -density ~~reactor~~ of reactors uses epoxy glass slide as the substrate. Hydrophobic liquid material "polyacrylate paint" (supplied by China Chengdu Chenguang Research Institute of Chemical Industry, with a water contact angle as 85°) is coated onto the substrate to form the highly-hydrophobic convex with a height about 100 μ m, and a width about 1mm, and form a substrate-well of 2 \times 2mm. After that, 3 types of antigen solutions will be deposited with an arrayer (GM417ARRAYER, GENETIC MICROSYSTEM COMP.) into said reserved area in the pattern of 10 spots for each type of ligand, so as to form 5 \times 6 probe arrays. The probe array (the substrate probe region) is 1 \times 1mm in size. The density of reaction well on the substrate is over 9 units/cm².

2) Evaluation and application of the analysis-chip with the high -density ~~reactor~~ of reactors

In the experiment, take 10 chips mentioned-above, number the reaction wells, any of the two reaction wells border upon are added respectively the positive serum of the mixture of the same volumes of Sample 1, 2, 3 and the negative control serum. The subjecting volume of sample is 5 μ l; that of marker is 7 μ l. The experimental method is the same as that in ~~Implementation example~~ Embodiment 1. The cross-contamination rate is defined as follows: the numbers of reaction wells, in which the acquired results disagree with the added samples, is divided by total numbers of reaction wells examined. The cross-contamination rate on the analysis-chip prepared in this ~~example~~ embodiment is zero.

Implementation example 9: Preparation of analysis-chip with the striped - capillary reaction-chamber and the application thereof

1) Preparation of the monoplane analysis-chip with the striped -capillary reaction-

SUBSTITUTE SPECIFICATION (marked up)

chamber

The monoplan analysis-chip with the striped -capillary reaction-chamber without the protection unit prepared in the example embodiment is marked as A1 (as showed in Picture FIG. 1). The monoplan analysis-chip with the striped -capillary reaction-chamber containing the protection unit is marked as A2.

The unit containing probes is prepared as below: on this substrate, "organosilicon highly-hydrophobic paint" (Chengdu Chenguang Research Institute of Chemical Industry) is coated to form a partition strip on the scheduled 8 inlet and outlet areas as shown in Picture FIG. 1. The width of each substrate-well is 4mm. After it is dried overnight, deposit above HCV fusion antigen solution and HIV fusion antigen solution in the pattern of 3 spots per each ligand into the above scheduled areas with an arrayer (GM417ARRAYER, GENETIC MICROSYSTEM COMP.), forming 3×3 probe arrays. After 3 hours of coating reaction at 37° r, it is blocked with bovine serum, rinsed and dried for use.

The formation of the striped-capillary reaction-chamber: the cover glass (60×12.5×0.15mm in dimension) is used as the top unit 11; the unit with probes prepared as above is used as the bottom unit 12. The top unit 11 is connected to the bottom unit 12 through adhesion. The used adhesive is dual epoxy resin (omnipotent adhesive, Chengdu Chenguang Research Institute of Chemical Industry). In accordance with the instruction of product, spread the adhesive onto the highly-hydrophobic coating of the unit containing substrates. And then adhere it to the other unit. Of the prepared analysis-chip with the striped -capillary reaction-chamber, the width of its striped-capillary reaction-chamber 1 is 4000μm. The space between the top plane 5 and bottom plane 6 is 80μm. There is a closed partition structure 8 in the parts of the top plane and bottom plane among the striped-capillary reaction-chambers. There are the open partition structure 4, inlet 9, outlet 10 in the parts of liquid inlet and outlet. The water contact angle of the glass slide is 44°.

Preparation of the monoplan analysis-chip with the striped -capillary reaction-chamber containing the protection structure: the inlet and outlet area mentioned-above can be closed or opened according to the need by using the preparation method for the dismantled analysis-chip in Implementation-example Embodiment 7.

2) Preparation of the double-plane analysis-chip with the striped -capillary reaction-chamber

The double-plane analysis-chip with the striped -capillary reaction-chamber without the protection unit prepared in this example embodiment is marked as A3 (as showed in Picture FIG. 1). The double-plane analysis-chip with the striped -capillary reaction-chamber containing the protection unit is marked as A4.

The top unit is based on the amino-group cover glass. The bottom unit is based on the amino-group slide. Both top plane and bottom plane are immobilized with probes. By using the ligand solution mentioned-above, HCV and HIV antigens are deposited respectively in the same pattern onto the corresponding positions of the top and bottom units with an arrayer (GM417ARRAYER, GENETIC MICROSYSTEM COMP.), 2 spots each, forming 2×2 ligand arrays. After the coating reaction, it is sealed, rinsed and dried. The connection of the top and bottom units as well as the

SUBSTITUTE SPECIFICATION (marked up)

formation of the inlet and outlet ~~are~~ is the same as in ~~Implementation-example~~ Embodiment 1). Of the prepared analysis-chip with the striped -capillary reaction-chamber, the dimensions of the top plane and bottom plane of the striped-capillary reaction-chamber is 4mm×12.5mm (width×height). The space between the top plane and bottom plane is 0.08mm. The water contact angle of the glass slide is 44°.

3) Examination of characteristics of the analysis-chip with the striped -capillary reaction-chamber

PBS is used as the test media in the ~~implementation-example~~ embodiment. Set the analysis-chip obtained in 1) and 2) upright (inlet on the bottom, and outlet on the top). Deposit 5ul of PBS with an 8-tipped pipette into the entrance of the striped-capillary reaction-chamber in the inlet well, and observe PBS solution filling the striped-capillary reaction-chamber through the inlet into outlet.

4) Utilization of the analysis-chip with the striped -capillary reaction-chamber

Sample 1, 2, and 5 are used in the ~~implementation-example~~ embodiment. Before the samples are subjected, they are diluted properly. There are two approaches for subjecting sample:

(1) Subjecting sample by batches: the volume subject is 3ul. During the processing, when the sample is subjected into the feeding well, the sample will fill the whole striped-capillary reaction-chamber from the inlet to outlet automatically due to capillarity. There isn't air bubbles observed. Put the analysis-chip into an incubator for reaction at 37□ for 5 minutes.

(2) Subjecting sample continually: during the processing, the sample is warmed up to 37□ n. Subject the sample into the feeding well with the flow velocity of 1ul/min. The subject volume is 10ul. The subject time is 10 minutes. The sample will fill the whole striped-capillary reaction-chamber from the inlet to outlet owing to the capillarity. There isn't air bubbles observed. The reaction temperature is 37□ . The reaction time is 5 minutes.

After the reaction, the sample is absorbed with paper or drawn out by the pipette via the outlet. Washing solution could be subjected by batches or continually with the total volume of 20ul.

The marker is Rhodamine-labeled goat anti-human secondary antibody (Jackson Immunoresearch Laboratories). In order to use the marker as few as possible, the batch-subjecting approach is applied. The subject volume is 3ul, the reaction temperature is 37□ T and the reaction time is 5 minutes. Washing after the labeling reaction is the same as that for the sample reaction. After being dried, the results are visualized directly by using the laser confocal microscope scanner (Afymetric Comp, GMS 418 analysis-chip Scanner). The data are processed to get results showed in Table 6.

Table 6

Ch ip	HCV antibody positive serum		HIV antibody positive serum		Positive control		Negative control	
	HCV antibody	HIV antibody	HCV antibody	HIV antibody	HCV antibody	HIV antibody	HCV antibody	HIV antibody
Subject sample by batches								

SUBSTITUTE SPECIFICATION (marked up)

A1 *	+	-	-	+	+	+	-	-
A2 *	+	-	-	+	+	+	-	-
A3 *	+	-	-	+	+	+	-	-
A4 *	+	-	-	+	+	+	-	-
A4 **	+	-	-	+	+	+	-	-
Subject sample continually								
A1 *	+	-	-	+	+	+	-	-
A2 *	+	-	-	+	+	+	-	-
A3 *	+	-	-	+	+	+	-	-
A4 *	+	-	-	+	+	+	-	-
A4 **	+	-	-	+	+	+	-	-

“+” stands for the positive result; “-” is the negative result

“* ”and “**” are the results of samples of 10-fold-diluted and of 20-fold-diluted respectively.

Implementation example 10: Application of the analysis-chip with the irreversible closed striped-capillary reaction-chamber and the application thereof

The substrate (amino-group slide) and two probes (HCV antigen and HIV antigen) in the ~~implementation example~~ embodiment are the same as those in ~~Implementation example~~ Embodiment 1.

1) Preparation of the bottom unit

(1) The material of the wall and seal structure of the striped-capillary reaction-chamber of bottom unit are elastic material

On the amino-group slide, elastic material (air-drying silicone rubber solution, Chengdu Chenguang Research Institute of Chemical Industry) is used to coat the whole areas evenly except 8 areas (refer to ~~Picture~~ FIG 3B; each area has a width of 4mm) that are scheduled for fixing ligands. The thickness of elastic layer is less than 0.06mm. After it is dried overnight, deposit the above ligands solution, in the pattern of 3 spots per ligand, into the above-scheduled areas with an arrayer (GM417ARRAYER, GENETIC MICROSYSTEM COMP.), forming 3 x 3 probe arrays. After 3-hour coating reaction at room temperature, it is blocked with bovine serum, cleaned and dried for use. The obtained bottom unit is marked as A1.

(2) The use of highly-hydrophobic material for the bottom unit of the wall and enclosing structure of the striped-capillary reaction-chamber

In the ~~implementation example~~ embodiment, the preparation of bottom unit is

SUBSTITUTE SPECIFICATION (marked up)

same as the unit-containing substrate in item 1) of ~~Implementation-example~~ Embodiment 1. The thickness of highly-hydrophobic material layer is less than 0.06mm. The obtained bottom units that use amino glass slide and black paint glass slide are marked as A2 and A3 respectively.

(3) The use of highly-hydrophobic and elastic materials respectively for the bottom unit of the wall and seal structure of the striped-capillary reaction-chamber

On an amino-group slide, the highly-hydrophobic material (organosilicon highly-hydrophobic paint, Chengdu Chenguang Research Institute of Chemical Industry) is coated onto the border of the 8 areas (as showed in ~~Pieture~~ FIG. 3A, each area has a width of 4mm) scheduled for fixing ligand to generate a borderline layer. After it is dried, elastic material (air-drying silicone rubber solution, Chengdu Chenguang Research Institute of Chemical Industry) is coated onto the areas outside the highly-hydrophobic borders, forming a strip whose width is 2mm. The layer of the elastic coating is a little higher than the highly-hydrophobic layer (The thickness of layer is less than 0.05mm). And then it is coated with the ligand solution mentioned-above. The coating method is the same as (1) in 1) of this ~~implementation-example~~ embodiment. The obtained bottom unit is marked as A4.

(4) The material of the wall and the enclosing structure of striped-capillary reaction-chamber of bottom unit is adhesive material

On amino-group slide, adhesive material (water-insoluble adhesive tape using polytetrafluoroethylene as substrate, Chengdu ChenGuang Research Institute of Chemical Industry) is used to adhere the areas outside 8 areas scheduled for fixing ligands (as showed in ~~Pieture~~ FIG. 3B, each area with a width of 4mm) homogenously (the thickness of layer is less than 0.2mm). And then it is spotted with ligand solutions mentioned-above. The spotted method is the same as (1) in 1) of the ~~implementation-example~~ embodiment. The obtained bottom unit is marked as A5.

(5) The bottom unit containing the striped-capillary reaction-chamber without the seal structure

The ligands mentioned-above are coated onto the amino glass slide directly. The coating method is the same as (1) in 1) of the ~~implementation-example~~ embodiment. The obtained bottom unit is marked as A6.

2) Preparation of the top unit

(1) Top unit without the formation structure

The top unit (See ~~Pieture~~ FIG. 3C) is made from stainless steel plate which can be used repeatedly, with a size as 100mm×40mm×2mm (length×width×thickness) and has a inlet 13, and liquid-outlet 14, and liquid-in and out pipes, and a fixing structure 15. Its surface contacted with the bottom unit is a plane without any seal structure. Every pair of inlet and outlet is corresponding to the inlet and outlet areas of each reaction well on the bottom unit. The obtained top unit is marked as B1.

(2) The top unit with the formation structure

(2) The top unit (~~Pieture~~ FIG. 3D) is made from stainless steel plate which can be used repeatedly, with a size as 100mm×40mm×2mm (length×width×thickness) and has a inlet and outlet 13 and liquid-in and -out pipes. On its plane contacted with the bottom unit there is the seal structure 16. Its seal structure is an elastic material layer

SUBSTITUTE SPECIFICATION (marked up)

(room temperature self-drying silicone rubber solution, Chengdu Chenguang Research Institute of Chemical Industry) (with a thickness less than 0.1mm) corresponding to the areas outside the reaction wells on the bottom unit. Every pair of inlet and outlet is corresponding to the inlet area and outlet area of each reaction well on the bottom unit. The obtained top unit is marked as B2.

3) Examination of characteristics of the analysis-chip with striped-capillary reaction-chamber

PBS is used as a test media in the ~~implementation-example~~ embodiment. The top and bottom units of the analysis-chip obtained in 1) and 2) mentioned-above are connected with hermetization. This ~~implementation-example~~ embodiment uses mechanic pressure to complete said seal connection. According to different combinations of the top and bottom units, varied chips are generated (See Table 7). Set the combined object of the top and bottom units upright (inlet on the bottom, outlet on the top). Subject PBS into the entrance of the striped-capillary reaction-chamber. Open the inlet and it can be observed that PBS solution is filling the striped-capillary reaction-chamber through the inlet to the outlet.

4) Use of the analysis-chip with the striped -capillary reaction-chamber

Samples used in the ~~implementation-example~~ embodiment are the same as those in ~~Implementation-example~~ Embodiment 1. During experiment, 4 samples are subjected into the analysis-chip (Table 7) with the striped-capillary reaction-chamber respectively. Each type of sample is subjected into 2 reaction wells respectively. Before the samples are subjected, they are diluted properly.

Two approaches to subjecting sample:

(1) Subjecting sample by batches:

During operation, sample is subjected into the feeding well and is stopped when it reaches outlet. It will fill the whole striped-capillary reaction-chamber due to capillarity from the inlet to the outlet automatically. There isn't air bubbles observed. Put the analysis-chip into an incubator for reaction for 5 minutes at 37°C .

(2) Subjecting sample continually:

During operation, sample is warmed up to 37°C u. Subject the sample into the feeding well with the flow velocity of 10ul/min at first and 1ul/min later on. The subjecting time is 5 minutes.

After the reaction, the sample is absorbed with paper or drawn out by a pipette via the outlet. Washing solution could be subjected by batches or continually. The total volume subjected is 40ul.

The marker is Rhodamine-labeled goat anti-human secondary antibody (Jackson ImmunoResearch Laboratories). In order to use the label volume as lease as possible, this ~~example~~ embodiment uses the batched approach to subject sample. The subject volume is 5ul. Reaction temperature is 37°C s. Time for reaction is 5 minutes. The washing after the labeling reaction is the same as that for the sample reaction s. After it is dried, the results are visualized directly with a laser confocal microscope scanner (Afymetric Comp, GMS 418 analysis-chip Scanner). The data are processed to get the results showed in Table 7.

SUBSTITUTE SPECIFICATION (marked up)

Table 7

Chip	Top unit	Bottom unit	HCV antibody positive serum	HIV antibody positive serum	Positive control	Negative control								
	+													
	10		+	-	+									
	100		+	-	+									

“+” stands for positive result; “-” negative result.